



8

NOHUMAN 181 MOS

Makita



Work amount

Cut Melapi (1m) with a ø6mm straight bit and at a cutting depth of 6mm



on a full battery charge





Brushless motor provides output efficiency similar or superior to that of our corded models.





Lock/unlock button and Power		
button		
Lock/unlock button		
LED lamp for indication of being unlocked		

Smooth and precision depth with rack and pinion mechanism







Transparent base Part No. 194267-1*

Standard equipment









*With Fine depth adjustment

Charging Time

Makita Singapore Pte Ltd 7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email : msgproductteam@makita.com.sg Website : www.makita.com.sg

Facebook : www.facebook.com/MakitaSG

TIBY AITHIUM HON	Fast Charging DC18RC	DC185D
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 _{min}	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min

Cordless Trimmer

DRT52 6 mm (1/4")

Soft Start

Anti-restart function

Standard Equipment :

Wrench, Templet guide, Chip deflector, Straight bit, Trimmer guide assembly, Straight guide assembly, Battery,

Collet size No load speed Base shape Base material Housing material Sound pressure level Sound power level Uncertainty (K) Vibration level Uncertainty (K) Dimensions (L x W x H) Net weight Net weight (Battery)

6 mm (1/4") 30,000 min⁻¹ Square (82 x 90mm) Plastic Plastic 81 dB(A) 89 dB(A) 3 dB(A) Rotation w/o load: 2.5 m/s² or less Rotation w/o load: 2.5 m/s² w/BL1860B: 134 x 90 x 220 mm (5-1/4 x 3-1/2 x 8-5/8") 1.3 - 1.6 kg (2.9 - 3.5 lbs.) BL1815N - BL1860B

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.



Charger





VISIT OUR WEBSITE

DOWNLOAD LEAFLET

PRINTED IN SINGAPORE