



Cordless Breaker
HM004G

Satisfy Professional's Needs



28.6mm Hex
Shank Type

40V^{Li-ION}max + 40V^{Li-ION}max



High power
similar to
corded models

Impact energy

72.8 Joule

Low Vibration

6.5 m/s²



BL MOTOR **AVT** **AWS** **SOFT** NO LOAD **XPT**

XGT X2
80Vmax



40Vmax Li-Ion + 40Vmax Li-Ion

Powered by two 40Vmax XGT
Li-Ion batteries in series
(80Vmax)

BL
MOTOR

High power
brushless
motor

Impact energy

72.8 Joule



Low Vibration thanks to **AVT**
(Anti-Vibration Technology)


Vibration level **6.5 m/s²**

Active dynamic vibration absorber moves in the opposite direction to the drive piston to reduce vibration.

Vibration absorbing housing


provides a practical combination of high power and low vibration.

Vibration absorbing spring (4 places)





Counter weight mechanism

reduces vibration during chipping operation.



SOFT NO LOAD

Suppression of motor speed during no-load



Slim body for excellent visibility



219mm

Hex shank: 28.6mm

Self sharpening bull point
(Country-specific)

AWS

(Auto-start Wireless System)

Connects to compatible vacuum cleaner with Bluetooth. The vacuum cleaner automatically runs while the switch is on.

Bluetooth®



Accessories

Dust extractor attachment set

w/o hose
Part No. 197168-2

w/ hose
Part No. 197148-8



**With Sensomatic chip


Charging Time

40Vmax Li-Ion	Fast Charging			
	DC40RA	DC40RB	DC40RC	DC40WA
BL4020 2.0Ah 191L29-0	22 min	30 min	110 min	
BL4025 2.5Ah 191B36-3	28 min	38 min	130 min	
*1 BL4040/F 4.0Ah 191O6-8	45 min	67 min	210 min	
*1 BL4050F 5.0Ah 191L47-8	50 min	85 min	260 min	
*1 BL4080F 8.0Ah 191X65-8	76 min	170 min	420 min	

*1 Recommended battery

Main power switch

Battery capacity warning lamp



Maintenance warning lamp

LED job light

Twin LEDs with preglow and afterglow functions



XPT

(eXtreme Protection Technology)



Cordless Breaker

HM004G 1-1/8" : 28.6mm Hex Shank

- 28.6mm Hex Shank
- Constant Speed
- Soft Start
- Built-in Job Light
- Anti-restart function

Impact energy	72.8 J (53.7 ft.lbs.)
Blows per minute (BPM)	870
Shank diameter	28.6 mm (1-1/8")
Sound power level	103 dB(A) (Uncertainty (K): 1.62 dB(A))
Sound pressure level	95 dB(A) (Uncertainty (K): 1.62 dB(A))
Vibration level	6.5 m/s ² (Uncertainty (K): 1.5 m/s ²)
Dimensions (L x W x H)	882 x 227 x 540 mm (34-3/4 x 8-15/16 x 21-1/4")
Net weight	29.7 - 32.1 kg (65.5 - 70.8 lbs.)

Standard Equipment: Hex wrench, Bull point, Wireless unit set

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE