






Noise level
48 dB
(A)
[in High speed]









# 3 Wind speed settings (High/Medium/Low)

- Independent of ON / OFF button
- Resumes at the speed set in last operation.
- With LED indicator

#### Off timer switch

- 3 Off timer settings: 1 hour, 2 hours, 4 hours
- with LED display

# **Automatic oscillation**



Left / Right 45 °

# Adjustable fan head angle



Up 90°, Down 45°, Left / Right 90°

## **Quiet running**

Changed the shape of corner rear fan cover to take the air smoothly to reduce the noise.



CF001G



Predecessor Model

# Easy-to-clean-up fan blades

Front cover is removable simply by removing a single screw, allowing for convenient clean up.





**Carrying handle** 



AC adapter jack



#### **Charging Time Reference**



#### DC40RA

The enlarged and raised LED light provides clearer indication of charging status.





**BL4025** 2.5Ah

28<sub>min</sub>



**BL4040** 4.0Ah

45<sub>min</sub>

### **Cordless Fan**

#### CF001G 40Vmax / AC



Continuous Use (min.)
w/o oscillation
Continuous Use (min.)
w/ oscillation
Max Air Velocity
Air Flow
Fan Diagneter

Air Flow
Fan Diameter
Dimensions (L x W x H)
Net weight

w/BL4040 Low/Mid/High: 1,160/880/660 w/BL4025 Low/Mid/High: 730/550/410 w/BL4040 Low/Mid/High: 1,055/800/600 w/BL4025 Low/Mid/High: 665/500/370 High/Mid/Low: 190/150/120 m/min High/Mid/Low: 8.2/6.5/5.2 m³/min

High / Mid / Low: 8.2 / 6.5 / 5.2 m / min 235 mm (9-1/4") 143x333x463 mm (5-5/8"x13"x18-1/4") 2.0 - 3.0 kg (4.4 - 6.6 lbs.)

Standard Equipment: AC Adaptor

The weight may differ depending on the attachment(s), including the battery cartridge.

Items of standard equipment and specifications may vary by country or area.

#### **Makita Singapore Pte Ltd**

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sg Website: www.makita.com.sg Facebook: www.facebook.com/MakitaSG





**VISIT OUR WEBSITE** 

