



# Driver Drill / Hammer Driver Drill DF0300 10 mm (3/8") / HP0300 10 mm (3/8")



Photo: DF0300

Max lock torque

**42 N·m**

## Excellent usability and compact

Driver Drill  
DF0300



Hammer  
Driver Drill  
HP0300



Max lock torque

42 N·m

Compact overall length

DF0300: 220mm, HP0300: 235mm

**2 sleeve keyless Drill chuck**

allows for easy bit installation/  
removal by one hand.

**Capacity of drill chuck**

1.0 - 10 mm (1/32 - 3/8")

**20 Torque settings**



Photo: DF0300

Variable speed  
control by trigger

**Mechanical 2-speed gearing**

High / Low: 0 - 1,500 / 0 - 450



Ergonomic handle with soft  
grip for driver-drill  
applications



Hammer  
Driver Drill  
HP0300



Driver Drill  
DF0300



**Accessory**

**Hook set**

Part No.  
194759-0



**Bit holder**

Part No.  
452947-8



Photo: DF0300



Photo: DF0300



Photo: DF0300



Photo: HP0300

**Driver Drill**

**DF0300** 10 mm (3/8")

**Hammer Driver Drill**

**HP0300** 10 mm (3/8")

Double Insulation

Variable Speed

Reversing

Mechanical 2-Speed

Keyless Chuck

Torque Setting 20

Standard Equipment : Bit

	DF0300	HP0300
<b>Continuous rating input</b>	320W	320W
<b>Capacity</b>	Steel / Wood: 10 / 28mm (3/8" / 1-1/8")	Concrete / Steel / Wood: 8 / 10 / 28mm (5/16" / 3/8" / 1-1/8")
<b>Chuck Capacity</b>	1.0 - 10 mm (1/32 - 3/8")	1.0 - 10 mm (1/32 - 3/8")
<b>No Load Speed (RPM)</b>	High / Low: 0 - 1,500 / 0 - 450	High / Low: 0 - 1,500 / 0 - 450
<b>Blows Per Minute (BPM)</b>	-	High / Low: 0 - 22,500 / 0 - 6,750
<b>Max Fastening Torque</b>	Hard / Soft: 56.0 / 21.0 N·m (500 / 190 in.lbs.)	Hard / Soft: 56.0 / 21.0 N·m (500 / 190 in.lbs.)
<b>Max lock torque</b>	42.0 N·m (370 in.lbs.)	42.0 N·m (370 in.lbs.)
<b>Vibration Level</b>	2.5 m/s <sup>2</sup> or less	Impact Drilling into Concrete: 12.5 m/s <sup>2</sup> Drilling into Metal: 2.5 m/s <sup>2</sup> or less
<b>Sound Pressure Level</b>	80 dB(A)	82 dB(A)
<b>Sound Power Level</b>	91 dB(A)	93 dB(A)
<b>Dimensions (L x W x H)</b>	220x67x206 mm (8-5/8"x2-5/8"x8-1/8")	235x67x206 mm (9-1/4"x2-5/8"x8-1/8")
<b>Net weight</b>	1.2 kg (2.7 lbs.)	1.3 kg (2.8 lbs.)
<b>Power supply cord</b>	2.5 m (8.2 ft)	2.5 m (8.2 ft)

Weight according to EPTA-Procedure 01/2014  
Items of standard equipment and specifications may vary by country or area.

**Makita Singapore Pte Ltd**

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE