



Cordless Heat Gun DHG181 / DHG180

Max 550°C air temperature



Max. Air Flow
200 L/min

Photo : DHG181

For various applications



Continuous run time

At max air temperature 550°C, Air Flow: 200L/min (DHG181, Stage 2)

about **21 min** Battery: BL1860B
(on a full battery charge)



Quick release mechanism for easy Nozzle replacement

Nozzle can be removed without touching the hot metal part simply by turning Plastic ring. Compatible with current nozzles for AC machines




Air volume setting

(DHG181 only)

The air volume is switchable by sliding the air volume switch to:
Stage 1: 120 L/min,
Stage 2: 200 L/min



Single LED job light with after-glow function



Lock-off lever
Trigger switch



Lock-on button

Hanging hook



Air temperature adjustment dial

(DHG181 only)
Stepless adjustment for setting to suitable temperature for your application



Photo : DHG181



Wide Variety of Accessories

Glass protection nozzle

Part No. PR00000028



Wide-slot nozzle

Part No. PR00000029



Reflector nozzle

Part No. PR00000030



Reduction nozzle 20

Part No. PR00000031



Overlap welding nozzle

Part No. PR00000032



Solder sleeves reflector

Part No. PR00000033



Welding nozzle

Part No. PR00000034



Pressure roller

Part No. PR00000035



Scraper

Part No. PR00000040



Scraper set

Part No. PR00000041



Scraper

Part No. PR00000042



Charging Time

18V LITHIUM-ION	Fast Charging		DC18SD
	DC18RC	DC18RD	
BL1815N 1.5Ah 196449-1	15 min		30 min
BL1820B 2.0Ah 197254-9	24 min		45 min
BL1830B 3.0Ah 197599-5	22 min		60 min
BL1850B 5.0Ah 197280-8	45 min		110 min
BL1860B 6.0Ah 197422-4	55 min		130 min

Cordless Heat Gun

DHG181 / DHG180

Electronic 2-Speed (DHG181 only)	DHG181
Built-in Job Light	DHG180
Standard Equipment : Glass protection nozzle, Wide slot nozzle, Reflector nozzle, Reduction nozzle	
Air Temperature	Dial 1/2/3/4/5/6; Ambient temperature/150/250/350/450/550°C
Air Flow	Stage 1: 120 L/min, Stage 2: 200 L/min
Dimensions (L x W x H)	w/ BL1815N / BL1820B: 173 x 79 x 237 mm (6-3/16 x 3-1/8 x 9-3/8") w/ BL1830B / BL1850B / BL1860B: 173 x 79 x 255 mm (6-3/16 x 3-1/8 x 10")
Net weight	1.0 - 1.4 kg (2.2 - 3.1 lbs.)
Air Temperature	550°C
Air Flow	200 L/min
Dimensions (L x W x H)	w/ BL1815N / BL1820B: 168 x 79 x 234 mm (6-5/8 x 3-1/8 x 9-1/4") w/ BL1830B / BL1850B / BL1860B: 168 x 79 x 251 mm (6-5/8 x 3-1/8 x 9-7/8")
Net weight	1.0 - 1.3 kg (2.2 - 2.9 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE