



Satisfy Professional's Needs

Cordless Hammer Driver Drill

Cordless Driver Drill

DHP486 13 mm (1/2") / **DDF486** 13 mm (1/2")



**Compact
But high power**



Max Lock Torque
125 N·m



Increased performance in continuous heavy-duty applications

Compact design

On top of the higher performance in continuous heavy-duty applications compared with the current model, shorter overall length is achieved by optimizing the design of the gear assembly.



All metal gear construction
for extra-high transmission durability



Mechanical 2-speed transmission



Max clutch torque: 12 N·m

Due to the increased contact area of the clutch cam, the max clutch torque is increased, enabling to tighten a heavy-duty fastener such as a dia. 9.0x50mm lag bolt in screwdriving mode.

Twin LED job light with preglow and afterglow functions



Variable speed control trigger

Hi-speed Max. 2,100 RPM

High power



Belt clip

Cordless Hammer Driver Drill
DHP486



Cordless Driver Drill
DDF486



XPT
EXTREME PROTECTION TECHNOLOGY

Cordless Hammer Driver Drill

DHP486 13 mm (1/2")

Cordless Driver Drill

DDF486 13 mm (1/2")

Variable Speed

Brake

Reversing

Mechanical 2-Speed

Keyless Chuck

Torque Setting 21

Built-in Job Light

Carrying Case

Capacity

DHP486
Steel: 13 mm (1/2")
Wood (Auger-Bit): 50 mm (2")
Wood (Self-Feed Bit): 76 mm (3")
Wood (Hole Saw): 152 mm (6")
Masonry: 16 mm (5/8")
Siding Board: 170 mm (6-11/16")

Chuck Capacity

1.5 - 13 mm (1/16 - 1/2")

Impacts Per Minute (IPM)

High / Low: 0 - 2,100 / 0 - 550

No Load Speed (RPM)

Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)

Max Fastening Torque

125 N·m (1,100 in.lbs.)

Max Lock Torque

w/o Battery: 178 x 81 x 217 mm (7 x 3-3/16 x 8-1/2")

w/ BL1830B / BL1850B / BL1860B: 178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")

Dimensions (L x W x H)

178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")

Net weight

2.3 - 2.7 kg (5.1 - 6.0 lbs.)

DDF486

Steel: 13 mm (1/2")
Wood (Auger-Bit): 50 mm (2")
Wood (Self-Feed Bit): 76 mm (3")
Wood (Hole Saw): 152 mm (6")

Siding Board: 170 mm (6-11/16")

1.5 - 13 mm (1/16 - 1/2")

High / Low: 0 - 2,100 / 0 - 550

Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)

125 N·m (1,100 in.lbs.)

w/o Battery: 178 x 81 x 217 mm (7 x 3-3/16 x 8-1/2")

w/ BL1830B / BL1850B / BL1860B: 178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")

2.3 - 2.6 kg (5.1 - 5.7 lbs.)

Standard Equipment: Depth Gauge (DHP486 only), Side Handle, Belt Clip, (+)(-) Bit, Bit Holder, Charger, Battery

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE