



Cordless Hammer Driver Drill
Cordless Driver Drill
DHP487 / DDF487 13 mm (1/2")

Satisfy Professional's Needs



Compact and light weight



photo: DDF487

Cordless Hammer Driver Drill
DHP487



Cordless Driver Drill
DDF487



Max Lock Torque

40 N·m

Light weight

1.3 kg

Battery: BL1820B / Model: DDF487



Compact and Slim design

Compact



Ergonomic handle for screwing applications



A In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened to perfectly fit the U-shape formed between user's thumb and index finger.


B Ribbed soft grip enables all finger tips to hold the handle securely against the strong rotational force of counter torque even in single-handed operation.

Redesigned appearance gives an impression of robustness

Robustness is highlighted by the aluminum diecast cover added around the gear housing case.




Twin LED job light




with preglow and afterglow functions

Variable speed control trigger



Mechanical 2-speed gearing





Accessories

Hook

For BL1815N / BL1820B
Part No. 346449-3



For BL1830B / BL1850B
/ BL1860B
Part No. 346317-0

Bit holder

Part No.
452947-8



	DHP487 13 mm (1/2")	DDF487 13 mm (1/2")
Variable Speed	DHP487	DDF487
Brake	Steel / Wood (Auger Bit / Self-Feed Bit / Hole Saw) / Masonry: 13 / 36 / 35 / 51 / 13 mm (1/2 / 1-7/16 / 1-3/8 / 2 / 1/2")	Steel / Wood (Auger Bit / Self-Feed Bit / Hole Saw): 13 / 36 / 35 / 51 mm (1/2 / 1-7/16 / 1-3/8 / 2")
Reversing	Capacity 1.5 - 13 mm (1/16 - 1/2")	1.5 - 13 mm (1/16 - 1/2")
Mechanical 2-Speed	Impacts Per Minute (IPM) High / Low: 0 - 25,500 / 0 - 7,500	-
Keyless Chuck	No Load Speed (RPM) High / Low: 0 - 1,700 / 0 - 500	High / Low: 0 - 1,700 / 0 - 500
Torque Setting 20	Max Fastening Torque 40 N·m (350 in.lbs.)	Hard / Soft: 40 / 25 N·m (350 / 220 in.lbs.)
Built-in Job Light	Max Lock Torque 40 N·m (350 in.lbs.)	40 N·m (350 in.lbs.)
Carrying Case	Vibration Level Impact Drilling into Concrete: 10.5 m/s ² Drilling into Metal: 2.5 m/s ² or less	-
	Sound Pressure Level 83 dB(A)	Drilling into Metal: 2.5 m/s ² or less 73 dB(A)
	Sound Power Level 94 dB(A)	-
	Dimensions (L x W x H) w/ BL1815N / BL1820B: 164 x 81 x 232 mm (6-1/2 x 3-3/16 x 9-1/8") w/ BL1830B / BL1850B / BL1860B: 164 x 81 x 248 mm (6-1/2 x 3-3/16 x 9-3/4")	w/ BL1815N / BL1820B: 150 x 81 x 248 mm (5-7/8 x 3-3/16 x 9-3/4") w/ BL1830B / BL1850B / BL1860B: 150 x 81 x 232 mm (5-7/8 x 3-3/16 x 9-1/8")
	Net weight 1.4 - 1.7 kg (3.1 - 3.7 lbs.)	1.3 - 1.6 kg (2.9 - 3.5 lbs.)
	Standard Equipment : Belt Clip, (+)(-) Bit, Battery, Charger	

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



Facebook: MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE