Cordless Combination Hammer DHR182 18 mm (11/16") Adapted for SDS-PLUS bits







Hammering





Depth gauge


can be adjusted for desired drilling depth simply by pushing single push button

Max Bit length





by turning the dial, the dust falls off from the filter







can be opened simply by pushing single push button for easy dust cleaning.







Twin LED job light





Excellent drilling performance

Work Speed

compared to our predecessor model

Work Volume

compared to our predecessor mode

- Concrete with compressive strength of 40N/mm²
- Diameter: Ø10.5mm(3/8"), depth of 60mm(2-3/8")

Work Amount

Battery: BL1850B



Auto - start Wireless System

Wireless Unit (option)

199393-1(Asia)





Switch on the tool



Vacuum cleaner is activated



Accessories

Dust collection system



Dust cup Part No.

198362-9 use with Grip base set Part No. 194581-5

Dust case

Part No. 199595-9



HEPA Filter

Part No. 199596-7



Cordless Combination Hammer

Wariable Speed

Make Brake

Reversing

SDS-PLUS Shank

Torque Limiter



Constant Speed **Dust Collection**





Carrying Case

Standard Equipment : Dust Cup (country-specific), Side Grip, Depth Gauge, Battery, Charger

Impact Energy

Capacity

Blows Per Minute (BPM) No Load Speed (RPM) **Max Output** Vibration Level

Sound pressure Level Sound power Level
Dimensions (L x W x H)

DHR182 18 mm (11/16") Adapted for SDS-PLUS bits EPTA-Procedure 05/2009: 1.7 J Our experimental conditions: 1.6 J

Concrete: 18 mm (11/16") Core Bit: 35 mm (1-3/8") Diamond Core Bit (Dry Type): 32 mm (1-1/4")

Steel: 13 mm (1/2") Wood: 24 mm (15/16") 0 - 5,000 0 - 1,350

450 W Hammer Drilling into Concrete: 11.0 m/s²

Drilling Into Metal: 2.5 m/s² or less 89 dB(A) 100 dB(A) w/BL1830B/BL1840B/BL1850B/BL1860B:

301x82x285 mm(11-7/8"x3-1/4"x11-1/4") 2.4 - 3.2 kg (5.3 - 7.0 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproduct team@makita.com.sgWebsite: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG







VISIT OUR WEBSITE

