



Variable speed control dial

allows operator to adjust cutting speed depending on material or application.




Dual LED job lights

Active Feedback sensing Technology

AFT

Torque limiter turns the motor off if the tool is suddenly forced to lock



XPT

EXTREME PROTECTION TECHNOLOGY


Dust and drip-proof performance is enhanced for use in outdoor applications or harsh environments.

Accessories

Dust Extractor Attachment Set

Part No. 196536-6

Drilling mode



Hammering mode



Dust Extractor Attachment Set Hammering only

with Vacuum hose set

Part No. 196571-4



Cordless Rotary Hammer

DHR400N 40 mm (1-9/16")

- Variable Speed
- Brake
- Reversing
- SDS-MAX Shank
- Torque Limiter
- Constant Speed
- Soft Start
- Dust Collection
- Built-in Job Light
- Carrying Case

| | |
|------------------------|--|
| Impact Energy | EPTA-Procedure 05/2009: 8.0 J Our experimental conditions: 11.4 J |
| Capacity | Concrete (w/ T.C.T. bit): 40 mm (1-9/16") Concrete (w/ Core bit): 105 mm (4-1/8") |
| Blows Per Minute (BPM) | 1,450 - 2,900 |
| No Load Speed (RPM) | 250 - 500 |
| Sound Pressure Level | 91 dB(A) |
| Sound Power Level | 102 dB(A) |
| Vibration Level | Hammer Drilling Into Concrete: 5.0 m/s ² |
| Dimensions (L x W x H) | 473x120x285 mm (18-5/8"x4-3/4"x11-1/4") |
| Net weight | 7.3 - 8.1 kg (16.1 - 17.9 lbs) |

Standard Equipment:

Side Handle, Side Grip, Depth Gauge, Bit Grease, Cloth, Wireless Unit (country-specific), Battery, Charger

Items of standard equipment and specifications may vary by country or area.

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE

Makita

Cordless Rotary Hammer DHR400N 40 mm (1-9/16")

Satisfy Professional's Needs

LXT



Adapted for
SDS-MAX bits

High Power similar to AC Tool

with Active Feedback sensing Technology

Extra Comfort with low level of vibration

18v + 18v → 36v

AVT

SOFT NOLOAD

BL MOTOR

AFT

AWS

XPT



Adapted for
SDS-MAX bits

Excellent performance equivalent to AC Model

18V + 18V → 36V

Newly developed BL motor
delivers high power



Drilling work amount

Work volume on a single full battery charge

About **25** holes

- ◆ w/ T.C.T. bit Ø18mm
- ◆ Depth : 140mm
- ◆ Concrete : 40 N / mm²
- ◆ Battery : BL1850B x2

Demolition work

with bull point

Impact Energy

[EPTA-Procedure 05/2009]

8.0 J

Makita HR4013C 8.0J

AVT & SOFT NO LOAD

ANTI VIBRATION TECHNOLOGY

Vibration absorbing
housing isolates handle
and motor.

Active dynamic vibration
absorber moves in the
opposite direction to the
drive piston to reduce
vibration.

Damper spring absorbs
impact vibrations from
the drill bit.



AWS
Auto-start Wireless System



Wireless unit
Part No.
199393-1

Bluetooth



Switch on the tool
Vacuum cleaner is activated

■ Comparison of Vibration level* and Time to reach ELV
(Exposure Limit of Vibration)**

* It is known as the tri-axial value and value at
Directive of A(8).

**It means the maximum amount of vibration that an
operator may be exposed to on any single day.

| Time to reach ELV (min) | 100 | 200 | 550 | |
|--|---------------------|-----|--------|----|
| Makita DHR400N | 5.0m/s ² | | 540min | |
| Makita HR4013C | 5.0m/s ² | | 540min | |
| Vibration level (m/s ²) | 0 | 5 | 10 | 15 |

AWS connects to power tool via Bluetooth.

Wireless unit



Bluetooth

The Bluetooth® word mark and logos are registered trademarks owned
by the Bluetooth SIG, Inc. and any use of such marks by Makita is under
license. Other trademarks and trade names are those of their respective
owners.

Expand AWS Line-up

AWS

