







Easy to carry around



Kettle can be transferred easily on Power supply stand by holding the carrying handle of the stand.

Dual layer structure



Stainless steel interior plus plastic exterior* provides high heat retention while keeping Kettle surface cool *There is a insulating layer of air between the interior and exterior layers.

Removable



Removable for easy water supply and cleaning

Anti-spill lock button



Provided to minimize spilling of hot water even if Kettle falls over.

Easy to read water scale



Kettle can be turned on only when grounded.



Dual battery fuel gauges



• Auto shut-off after boiling • Boil-dry protection



Boiling time (23°C) (approx.)

8 min

Power switch



Battery BL1850B x2 capacity of boiling water (23°C)



Accessories





not covered by EPTA-Procedure Items of standard equipment and specifications may vary by country or area.

Charging Time

18V LITTHIUMHON	DC18RC DC18RD	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 _{min}	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 _{min}

Cordless Kettle

DIZ	-
1116	360

Boiling time (approx. / min)	8 (0.8L water from 23 °C)
Water tank capacity	0.8 L
Dimensions (L x W x H)	Kettle on Power supply stand:
	233 x 263 x 307 mm (9-1/8 x 10-3/8 x 12-1/8")
Net weight	2.7 - 3.4 kg (6.0 - 7.5 lbs.)
•	•

Approx amount of hot water for making drinks/foods		
Instant/drip coffee	0.2 L	
Instant cup soup	0.15-0.23 L	
Instant cup noodles	0.3-0.5 L	


Boiling time (approx.) of 0.8L water				
Starting water temperature	10°C	23°C	40°C	
Boiling time	9 min	8 min	6 min	

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproduct team@makita.com.sgWebsite: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG









VISIT OUR WEBSITE DOWNLOAD LEAFLET