



Cordless Flashlight
DML812

Satisfy Professional's Needs

LXT

Long beam distance & High brightness



Beam distance

640 m

Luminous flux

1,250 lm
Spot + flood

18V
LITHIUM-ION

XPT

Over 640m Beam Distance & Max 1,250 Lumens

4 modes

Spot



Luminous flux

600 lm



640m



Spot + Flood



1,250 lm



Flood



1,000 lm



Strobe



1,250 lm



This mode is set by pressing the mode button long for smooth transition from any mode to use for alerting etc.

Continuous run time (with BL1860B)

Spot	Spot + Flood	Flood	Strobe
10 h	6.0 h	7.5 h	8.5 h

Accessories

Shoulder Strap
Part No. GM00002239



On/off switch

4 Mode switch

Press the mode switch to cycle

► Spot

▼ Spot + Flood

▼ Flood

Strobe

Press and hold the mode switch until the appliance turns strobe mode.



XPT
Extreme Protection Technology

18V
LITHIUM-ION

Hook



Pipe



Chain

Variable-angle head

90°



Luminous flux

Spot + flood

1,250 lm

Beam distance

640 m

Cordless Flashlight

DML812

Run Time (hrs)	Up to: 10 (Spot, with BL1860B)
Illuminance	at 1m from the light source
	Spot Mode/ Flood Mode/ Spot-Flood Mode:
	71,000/ 520/ 51,000 lx
Luminous Flux	Spot Mode/ Flood Mode/ Spot-Flood Mode:
	600/ 1,000/ 1,250 lm
Dimensions	w/ BL1830B / BL1850B / BL1860B: 313x119x115 mm
(L x W x H)	(12-3/8"x4-11/16"x4-1/2")
Net weight	1.2-1.6 kg (2.6-3.4 lbs)

Standard Equipment: Shoulder Strap

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



f MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE