



Cordless Worklight
DML813 / DML814

Satisfy Professional's Needs



Max luminous flux
3,000 lm

Max Height
2,240 mm

IP55

certified weather
and dust resistance

DML813

[Spot lighting]



DML814

[Spot lighting]



[Area lighting]



18V
LITHIUM-ION



Continuous run time (with BL1850B)

High	Medium	Low
3.0 h	5.5 h	10 h

3 brightness settings

High	Medium	Low
3,000 lm	1,700 lm	900 lm

Pivoting range of light head for Spot lighting



right and left
115°

up and down
110°

Pivoting range of 3 small light heads for area lighting



up and down
90°
DML814 only

Foldable into a compact size for simple storage and transport



1,000 mm

Push the unlock button to expand / fold the tripod base.



Shoulder belt

Attachable to the worklight or tool bag for comfortable carrying of the worklight



Accessories

Tool Bag



Shoulder Belt



2,240 mm



The height of light head can be adjusted steplessly



1,250 mm

18V
LITHIUM-ION

DML814

Two lighting modes

Spot lighting / Area lighting

Battery capacity warning function

automatically notifies the user about reduction in battery capacity with the decrease of illuminance (Only one LED is on for notification).



DML813

Spot lighting



Easy installation and removal of battery



The battery port is located at the middle height of the worklight so that the user need not bend down to access the battery.

Padlock hole for battery theft protection



*Padlock not included

Three hook holes for the shoulder belt

Two hook holes are located on the carrying handle beside the battery, and one on the end of a tripod leg.


Tripod fixing hole



The tripod can be firmly secured to the ground with a screw or peg.

Cordless Worklight

DML813 / DML814



Carrying Case

Standard Equipment:
Shoulder Belt

Run Time (hrs)

Illuminance

(High / Mid / Low)

Luminous Flux
Dimensions (L x W x H)

Folding Position:

Operating Position (Max Height):

Net weight

Battery & Charger Sold Separately

w/ BL1850(B) Low / Mid / High: 10 / 5.5 / 3
at 1m from the light source: 1,250 / 750 / 400 lx
at 3m from the light source: 130 / 80 / 40 lx
at 5m from the light source: 50 / 30 / 15 lx
High / Mid / Low: 3,000 / 1,700 / 900 lm
260x216x1,000 mm (10-1/4"x8-1/2"x39-3/8")
573x658x1,250-2,240 mm (22-1/2"x26"x49-1/4"-88")
DML813: 7.0 - 7.7 kg (15.4 - 17.0 lbs.)
DML814: 7.2 - 7.9 kg (15.9 - 17.4 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE