











Comfortable short telescopic pipe provides easy handling in tight spaces



Telescopic pipe

adjustable in length from 1,518mm (59-3/4") to 1,618mm (63-3/4")





Run time (min)

On a single full battery charge

for prevention of scattering of grass

Cutting blade	Battery	No load		
		High	Middle	Low
with Nylon cord diameter: ø2.0 mm (Two Strings come out from separate openings) 191D92-5	BL1850B	55	83	139
with Plastic blade Trimming width: ø255mm (Three-blade cutter) 198848-3	BL1850B	102	121	181


clippings.



Automatic torque Drive Technology

automatically changes the cutting speed according to load conditions for an optimum operation:

- On light duty: high-speed rotation mode
- On heavy duty: high torque mode



All control devices are conveniently located near your hand.



Main power button

Speed indicator

shows three rpm levels. Also shows the status of overload, overheat and overdischarge.

Auto speed control indicator (ADT mode)

Power lamp

Reverse button

for easy removal of grass clippings from the cutting tool (with plastic blade) After 1.5 seconds, machine stops. Switch position will be returned back to "Forward" automatically after stopping.



Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather.

Cordless Grass Trimmer DUR189

Brake
Reversing
Electronic 3-Speed
Constant Speed
Soft Start
Standard Equipment :

No Load Speed **Cutting Width**

Spindle Size Sound Pressure Level Vibration Level Front / Rear Dimensions 3.0 - 3.3 kg (6.6 - 7.3 lbs.)

High / Medium / Low / ADT Mode: 6,000 / 5,000 / 4,000 / 4,000 - 6,000 Trimmer Head: 300 mm (11-3/4") Plastic Blade: 255 mm (10")

M8 x 1.25 RH 78 dB(A) $2.5/2.5 \, \text{m/s}^2 \, \text{or less}$ 1,518-1,618x258x396mm (59-3/4" - 63-3/4"x10-1/8"x15-5/8")

Shoulder Strap, Nylon Cutting Head, Plastic Blade, Safety Goggles, Accessory Bag, Hex Wrench, Battery, Charger

 $The \ weight\ may\ differ\ depending\ on\ the\ attachment (s), including\ the\ battery\ cartridge.$ The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sg

Website: www.makita.com.sg Facebook: www.facebook.com/MakitaSG







