

Cordless Garden Sprayer DUS054 / US053D 5 L





Max permissible pressure

0.3_{MPa}

Tank capacity

5_L

DUS054



US053D











2-mode selectable





Stream mode is optimal for watering or fertilizing plants, such as trees, located a little away from the user.

Ergonomically optimized tank design



Both sides are ergonomically curved to fit user's body when the sprayer hangs from the shoulder, increasing user's productivity.

Easy battery removal





The battery pops out for easy removal simply by pushing the hook of the battery.

Continuous run time / Spraying capacity on a full battery charge Single outlet

	Mist	Stream	
DUS054	240 min	235 min	
BL1830B	/ 110 L	/ 140 L	
US053D	95 min	90 min	
BL1016	/ 40 L	/ 50 L	

Charging Time

18V LUMHUMHON	DC18RC DC18RD	DC18SD	12Vmax LUTTHUMHON	DC10SB	DC10WD
BL1815N 1.5Ah	15 min	30 min	BL1016 1.5Ah	22 _{min}	50 _{min}
BL1820B 2.0Ah	24 min	45 min			
BL1830B 3.0Ah	22 min	60 min	BL1021B 2.0Ah	30 _{min}	70 _{min}
BL1850B 5.0Ah	45 min	110 min			
BL1860B 6.0Ah	55 min	130 min	BL1041B 4.0Ah	60 _{min}	130 _{min}

Cordless Garden Sprayer

DUS054 / US053D 5 L

0.3 MPa (3 kgf/cm²) Max Pressure Chemical tank Hose Length Spray Wand Length G 1/4 DUS054: 343 x 182 x 368 mm Nozzle Mounting Thread Dimensions (L x W x H) (13-1/2 x 7-1/8 x 14-1/2") US053D: 343 x 182 x 343 mm (13-1/2 x 7-1/8 x 13-1/2") DUS054: 3.2 - 3.5 kg (7.1 - 7.7 lbs.) US053D: 2.9 - 3.0 kg (6.4 - 6.6 lbs.) Net weight

Standard Equipment:

H-Shaped Double Head Nozzle, Spray Wand, Spray Wand Holder, Shoulder Belt, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproduct team@makita.com.sg

Website: www.makita.com.sg Facebook: www.facebook.com/MakitaSG







DOWNLOAD LEAFLET