Accessories

Note: All though type B hose can be connected with power tools, Front cuffs and Joint are required

for some power tools

A: for power tools



Straight pipe, Bending pipe, Anchor nozzle set and

Corner nozzle



Nozzle assembly





Туре	Dry/ Wet	Part No.
Universal Type	Dry/ Wet	195551-7
Compact Type A	Dry	195549-4
Compact Type B	Wet	195550-9
Wide Type	-	A-47846

Holder set 10-33





195435-9

Cleaning set -Hose complete 38-2.5



-Nozzle assembly





191657-9

195439-1

Front cuffs & Joint



Туре	Part No.
Front cuffs 22	195547-8
Front cuffs 24	195546-0
Front cuffs 38	195545-2
Joint 22-38	195548-6

Filter set









owder filter set	Prefilter set	Cloth filter	Filter set (for water)
Part No.	Part No.	Part No.	Part No.
*197166-6	195553-3	140248-3	195555-9





Poly bag set

:	E-0
	8
	ME
	SERVICE STATE
	1

à		
5	Per pkg.	Part No.
	10	195432-5

Filter bag set



Corded and Cordless Vacuum Cleaner DVC860L (Wet & Dry / Cloth filter type) **DVC861L** (Only Dry / HEPA filter)



 $(L \times W \times H)$ Net weight

AC: 320W DC: 25-70W AC: 24kPa DC: 9kPa Dust: 8L

DVC861L (BL1850Bx2): 9.9kg (21.8bs)

366x334x368mn (14-3/8"x13-1/8"x14-1/2") DVC860L (BL1820x2); 8.6kg (19.0lbs) DVC860L (BL1850Bx2): 9.2kg (20.3lbs) DVC861L (BL1820x2): 9.3kg (20.5lbs)

5.0m (16.4ft)

Power supply cord

Fast charger, Battery cartridge, Connection cord, Tool box, Hose complete, Poly bag set, Straight pipe, Bending pipe,

*weight according to EPTA-Procedure 01/2003

 $I tems\ of\ standard\ equipment\ and\ specifications\ may\ vary\ by\ country\ or\ area.$

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sgWebsite: www.makita.com.sg Facebook: www.facebook.com/MakitaSG









DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



Corded and Cordless Vacuum Cleaner DVC860L (Wet & Dry / Cloth filter type) DVC861L (Only Dry / HEPA filter)







Suction power **70** w

Max air flow **2.1** m²/min

Max sealed suction **9.0** kPa








On DC power + On AC power



Max air flow **3.6** m²/min

Max sealed suction **24.0** kPa







Removable power supply



Continuous run time

On a single full battery charge: minute

Battery		BL1850B [5.0Ah]	BL1840B [4.0Ah]	BL1830B [3.0Ah]
Run time	High	30min.	25min.	20min.
nuii tiirie	Low	65min.	50min.	40min.
Charging ti	me			
DC18RD		45min.	36min.	22min.
DC18RC		45min. × 2	36min. × 2	22min. × 2
DC18SD		110min. ×2	90min. $ imes$ 2	60min. × 2





Large on-off switch

• allows for easy on/off switching. • functions only when Main power switch is on to prevent accidental switch-on during transportation, etc.



Dual battery fuel gauge



Variable suction power control by dial



Caster stopper



Removable storage box



On-tool pipe storage

