









Provides high speed fastening





Max fastening torque

47.5_{N·m}





Supplied with two socket adapters





Part No.191A50-3

Socket adapter 6.35 mm (1/4") Part No.191A51-1





Can also be used as a hand ratchet wrench






Forward / reverse rotation change

Turn the reversing lever to the A side for clockwise rotation or to the B side for counterclockwise rotation.





Able to tighten 13mm nut onto M8 threaded rod

13mm nut only



Single LED job light

with preglow and afterglow functions



Tool bag

Part No. 832074-1



Cordless Ratchet Wrench Series







Cordless Ratchet Wrench

DWR180 9.5 mm (3/8")







Built-in Job Light



Carrying Case

Capacity Standard Bolt: M5 - M12 (3/16 - 1/2") High Strength Bolt: M5 - M10 (3/16 - 3/8") 9.5 / 6.35 mm (3/8 / 1/4") Sauare Drive No Load Speed (RPM) Max Fastening Torque Vibration Level Sound Pressure Level Dimensions

47.5 N·m (420 in.lbs.) 2.5 m/s 74 dB(A)

74 dB(A) W/o Battery: 350 x 79 x 67 mm (13-3/4 x 3-1/8 x 2-5/8") W/BL1815N / BL1820B: 369 x 79 x 69 mm (14-1/2 x 3-1/8 x 2-3/4") W/BL1830B / BL1840B / BL1850B / BL1860B: 369 x 79 x 87 mm

(14-1/2 x 3-1/8 x 3-7/16") 1.2 - 1.6 kg (2.6 - 3.5 lbs.) Net weight

Standard Equipment: Socket Adapter, Battery, Charger, Tool Bag (Country-specific)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproduct team@makita.com.sgWebsite: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG







VISIT OUR WEBSITE

 $(L \times W \times H)$



DOWNLOAD LEAFLET