



# Electric Breaker HM1511 / HM1501 1-3/16" : 30 mm Hex Shank

## High power and Low vibration

photo: HM1511  
Bit is option

Impact energy  
[EPTA-Procedure 05/2009]

**48.9** Joule

model: HM1511

Vibration Level  
( at main handle )

**6.5** m/s<sup>2</sup>

model: HM1511

**AVT** **SOFT**  
**NOLOAD**  
▲ HM1511 ▲

# High power and Low vibration

Thanks to completely redesigned hammering mechanism and increased motor power as compared with predecessor model, higher power is achieved with minimum increase in tool size and weight.

**AVT**  
ANTI VIBRATION TECHNOLOGY  
(HM1511 only)

**Active dynamic vibration absorber**  
(HM1511 only)

**SOFT NOLOAD**

(HM1511 only)  
Suppression of motor speed during no-load



**HM1511 / HM1501**

**30mm Hex Shank**



photo: HM1511

**Anti-vibration housing**

Slide switch



**1** Power-ON indicator lamp

**2** Service indicator lamp

**Carrying case**



**Accessories**

**Dust extractor attachment set**  
include vacuum hose  
Part No. 191M20-4



Model	Shank	AVT	SOFT NOLOAD	Impact energy	Vibration
HM1511	30 mm Hex Shank	✓	✓	48.9 J	6.5 m/s <sup>2</sup>
HM1501		—	—	48.1 J	14.5 m/s <sup>2</sup>

**Electric Breaker**

**HM1511 / HM1501 1-3/16" : 30 mm Hex Shank**

218

	HM1511	HM1501
Double Insulation	1,850W	1,850W
30mm Hex Shank HM1511 / HM1501	<b>Continuous rating input</b> 1,850W <b>Impact Energy</b> EPTA-Procedure 05/2009: 48.9 J	<b>Continuous rating input</b> 1,850W <b>Impact Energy</b> EPTA-Procedure 05/2009: 48.1 J
Soft Start	<b>Blows Per Minute (BPM)</b> 1,300	1,300
Carrying Case	<b>Sound Pressure Level</b> 85 dB(A)	84 dB(A)
	<b>Sound Power Level</b> 105 dB(A)	104 dB(A)
	<b>Vibration Level</b> Chiselling Function w/ Side Handle: 6.5 m/s <sup>2</sup>	Chiselling Function w/ Side Handle: 14.5 m/s <sup>2</sup>
	<b>Dimensions (L x W x H)</b> 781 x 130 x 266 mm (30-3/4 x 5-1/8 x 10-1/2")	781 x 130 x 266 mm (30-3/4 x 5-1/8 x 10-1/2")
	<b>Net weight</b> 19.2 kg (42.3 lbs.)	18.4 kg (40.6 lbs.)
	<b>Power supply cord</b> 5.0 m (16.4 ft)	5.0 m (16.4 ft)

*Standard Equipment* : Side Handle

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

**Makita Singapore Pte Ltd**

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE