

Cordless Rotary Hammer









Powered by Slide Li-ion Battery of Makita's New 12Vmax Platform



Extremely Compact and Lightweight for increased maneuverability





250 mm

Lightweight with BL1016





SDS-PLUS shank One touch sliding chuck

for easy bit changes

Vibration absorbing housing

reduces the vibration to the hand.

Vibrating portion Handle section Center of gravity Tnakita **Well balanced** design Compact -shaped handle reduces the fatigue on the arm.

Makita [LITHIUM+[ON Tnakita. 4.0Ah 18V DHR242

LED job light



Brushless motor





Accessories

Wide hook set





Dust cup set Use with grip base set



HR166D

EPTA-Procedure 05/2009: 1.1 J

Concrete: 16 mm (5/8") Steel: 10 mm (3/8")

Wood: 13 mm (1/2")

0 - 680



■ Li-ion Battery & Charging Time Reference

	ZXT 12Vmax LITHIUMJON			
*with Battery fuel gauge		*BL1041B 12Vmax 4.0Ah	*BL1021B 12Vmax 2.0Ah	BL1016 12Vmax 1.5Ah
Charging time	DC10SB	60 min	30 min	22 min
	DC10WD	130 min	70 min	50 min

Cordless Rotary Hammer

Impact Energy Variable Speed Capacity

Brake



SDS-PLUS Shank



Carrying Case

Impacts Per Minute (IPM) No Load Speed (RPM) Vibration Level

Sound Pressure Level Sound Power Level Dimensions (L x W x H) Net weight

Standard Equipment:

Hammer Drilling Into Concrete: 7.5 m/s² Drilling Into Metal: 2.5 m/s² or less 86 dB(A) 97 dR(A) 250x74x187mm (9-7/8"x2-15/16"x7-3/8")

BL1016: 1.8 kg (4.0lbs.) BL1041B: 2.0 kg (4.4 lbs.)

Dust Cup (country-specific), Side Grip, Depth Gauge, Battery, Charger

weight according to EPTA-Procedure 01/ver.2.1

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sg Website: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG







VISIT OUR WEBSITE



DOWNLOAD LEAFLET