

photo : HS7010

One-finger trigger switch
(HS7010)

Rear dust exhaust port

Flat motor housing design
increases stability when changing blades.



Angular guide at rear
For smooth and precise adjustment of bevel angle

1,600W
Continuous rating input

Aluminum diecast safety cover

Dust nozzle (Optional)
can be attached for use with a vacuum cleaner.
Part No. 196520-1

Metal plate base
(HS7010)



Circular Saw **HS7010 185 mm (7-1/4") - 190 mm (7-1/2")**

- Double Insulation
- Dust Collection
- Carrying Case

	HS7010
Continuous rating input	1,600W
Blade Diameter	185 / 190 mm (7-1/4" / 7-1/2")
Max Cutting Capacity	90°: 65 / 67 mm (2-9/16" / 2-5/8") 45°: 44 / 45 mm (1-3/4" / 1-3/4")
No Load Speed (RPM)	5,500
Dimensions (L x W x H)	300x240x261 mm (11-3/4"x9-1/2"x10-1/4")
Net weight	4.0 kg (8.9 lbs)
Power supply cord	2.5 m (8.2 ft)

Standard Equipment : TCT Saw Blade, Rip Fence (Guide Rule), Hex Wrench, Dust Nozzle (country-specific)

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



Circular Saw HS7010

185 mm (7-1/4") - 190 mm (7-1/2")



Powerful 1,600 W motor delivers high power and performance

Steel plate base

One-finger switch