Delivers 140 N·m (1,240 in.lbs.) of Max Torque in an ultra compact size



161 mm **54** mm Single LED job light Best possible ergonomic handle for screwing applications with preglow and afterglow functions In order to provide maximum thrust to the bit, the top back of the handle is ergonomically Thakita designed and widened to perfectly fit the U-shape formed between user's thumb and index finger. Ribbed soft grip enables all В finger tips to hold the handle securely against the strong rotational force of counter torque even in single-handed operation. Variable speed control by trigger

Li-ion Battery & Charging Time Reference, Compatibility Chart



Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone : +65-6546-8700 Fax : +65-6546-8711 Email : msgproductteam@makita.com.sg Website : www.makita.com.sg Facebook : www.facebook.com/MakitaSG

Cordless Impact Wrench TW140D 3/8" (9.5 mm)



Square Drive No Load Speed (RPM) Impacts Per Minute (IPM) Max Fastening Torque Dimensions (L x W x H)

Net weight

Fastening Capacities

Standard Bolt: M8 - M16 (5/16" - 5/8") High Tensile Bolt: M6 - M12 (1/4" - 1/2") 9.5 mm (3/8") 0 - 2,600 0 - 3,200 140 N-m (1,240 in.lbs.) w/ BL1016/BL1021B: 161x66x205 mm (6-3/8"x2-5/8"x8-1/8") w/ BL1041B: 161x66x224 mm (6-3/8"x2-5/8"x8-7/8") 1.0 - 1.2 kg (2.3 - 2.7 lbs.)

Standard Equipment : Belt Clip, Battery, Charger

rarea. The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.





MakitaSG Q VI

f

VISIT OUR WEBSITE

DOWNLOAD LEAFLET



Cordless Impact Wrench TW140D 3/8" (9.5 mm)



More Compact and High Power





Max Fastening Torque

140 N·m

Work volume

on a single full battery charge M12, 100N·m about (with BL1041B) **320**pcs