



Accessories

Guide bar / Saw chain / Guide bar cover / File diameter / Drive sprocket

*Carving bar

**Sprocket nose bar (Micro-Lite)

***Sprocket nose bar



Cutter type:
MC: Micro chisel,
CC: Chamfer chisel



Drive sprocket




Guide bar		Saw chain						Bar cover	File diameter		Drive sprocket	
Bar length	Part No.	No. of drive links	Gauge	Pitch	Cutter type	Saw chain Part No.		Part No.	1st half of top plate	2nd half of top plate	Pitch/ No. of teeth	Part No.
25cm/10"	*168407-7	60	1.3mm/ .050"	1/4"	25AP	MC	191G96-5	458501-6	4.0mm	4.0mm	1/4" / 9	191V92-3
25cm/10"	**191G14-3	40	1.1mm/ .043"	3/8"	90PX	CC	191H00-0	458501-6	4.5mm	4.0mm	3/8" / 6	191V90-7
25cm/10"	***191G22-4	40	1.3mm/ .050"	3/8"	91PX	CC	191H08-4	458501-6	4.0mm	4.0mm	3/8" / 6	191V90-7
30cm/12"	**191G15-1	46	1.1mm/ .043"	3/8"	90PX	CC	191H01-8	419288-5	4.5mm	4.0mm	3/8" / 6	191V90-7
30cm/12"	***191G23-2	46	1.3mm/ .050"	3/8"	91PX	CC	191H10-7	419288-5	4.0mm	4.0mm	3/8" / 6	191V90-7
30cm/12"	***191T86-6	51	1.1mm/ .043"	.325	80TXL	MC	191T90-5	419288-5	4.0mm	4.0mm	.325 / 7	191V91-5
35cm/14"	**165246-6	52	1.1mm/ .043"	3/8"	90PX	CC	191H02-6	419288-5	4.5mm	4.0mm	3/8" / 6	191V90-7
35cm/14"	***191G24-0	52	1.3mm/ .050"	3/8"	91PX	CC	191H11-5	419288-5	4.0mm	4.0mm	3/8" / 6	191V90-7
35cm/14"	***191T87-4	59	1.1mm/ .043"	.325	80TXL	MC	191T91-3	419288-5	4.0mm	4.0mm	.325 / 7	191V91-5
40cm/16"	**191G17-7	56	1.1mm/ .043"	3/8"	90PX	CC	191H03-4	419242-9	4.5mm	4.0mm	3/8" / 6	191V90-7
40cm/16"	***191G25-8	56	1.3mm/ .050"	3/8"	91PX	CC	191H12-3	419242-9	4.0mm	4.0mm	3/8" / 6	191V90-7
40cm/16"	***191T88-2	64	1.1mm/ .043"	.325	80TXL	MC	191T92-1	419242-9	4.0mm	4.0mm	.325 / 7	191V91-5

File and File holder

The file can be guided more easily if a file holder is employed. The file holder has markings for the correct sharpening angle of 30° (align the markings parallel to the saw chain) and limits the depth of penetration (to 4/5 of the file diameter).



Size	Saw chain type	File	File and File holder
		Part No.	Part No.
4mm	25AP, 91PX, 80TXL	953 003 090	953 030 010
4.5mm	90PX	953 003 100	195923-6



Chain oil & BIOTOP Chain oil



Chain oil		BIOTOP Chain oil	
Size	Part No.	Size	Part No.
100ml	182229-1	1L	980 008 610
1L	988 002 656		

Flat file




Part No.
953 003 060

Depth gauge jointer

After sharpening the chain, check the height of the depth gauge using the chain gauge tool.



Part No.
953 100 090




File handle

For flat file and file



Part No.
953 004 010



Charging Time Reference

	DC40RA Fast Charging	DC40RC
BL4020 2.0Ah 191L29-0	22min	30min
*1BL4025 2.5Ah 191B36-3	28min	38min
*1BL4040 4.0Ah 191B26-6	45min	67min
BL4050F 5.0Ah 191L47-8	50min	85min

*1 Recommended battery

Cordless Chain Saw

UC003G 300mm (12")

	Variable Speed	Guide Bar Length 300 mm (12")
	Brake	Chain Pitch / Chain Gauge 9.5 mm (3/8") / 1.1 or 1.3 mm (.043" or .050")
	Automatic Oiling	Chain Speed 0-24.8 m/s (0-1,490 m/min)
	Chain Brake	Chain Oil Tank Volume 200 mL
		Sound Power Level 100dB(A)
		Vibration Level (Front/ Rear) 2.9/ 2.4 m/s ² (saw chain: 90PX)
		Dimensions (L x W x H) 266 x 194 x 227 mm (10-1/2 x 7-5/8 x 8-15/16") w/o guide bar
		Overall length (Saw chain with 90PX) 543 mm (21-3/8")
		Net weight 3.8 - 4.7 kg (8.4 - 10.4 lbs.)

Standard Equipment : Saw Chain, Guide Bar, Guide Bar Cover, Oil supply (country-specific), Round File (country-specific), Box Wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



Cordless Chain Saw UC003G



As powerful as 30cc petrol chain saw



Net weight (tool only)
2.6 kg

Max Chain Speed
24.8 m/s

Sprocket nose bar
UC003G: 300mm (12")



BL
MOTOR

High operating efficiency

Outer Rotor Brushless
Motor direct-drive
system provides high
operating efficiency.



Cutting work amount

Work volume on a single full battery charge

About **160** cuts

- 100x100mm cedar timber
- Guide bar/ Saw chain:
350mm/ 90PX
- Battery : BL4040

WG / **IPX4**
WET GUARD

High water-resistance allows to operate the machine
even if it is wet with water.



Net weight

2.6
kg

Tool only

Max Chain Speed

24.8
m/s

Hanging D-ring
Rope attachment point



Captive nuts prevent loss of
nut




Variable speed trigger
switch



Large oil tank cap
allows for easy chain oil filling.
Metal spike bar
Chain oil level window



Chain tensioning screw
Metal chain catcher



Adjustable automatic
chain lubrication



Excellent tool balance

