40Vmax series movie



40Vmax mechanism movie



This movie was filmed in Japan. Models and specs may vary by country.

Portable Power Pack

Powered by up to four 18V LXT batteries







Powered by 36V-40Vmax built-in battery







Adapter between Battery box of Portable power pack and Product on 40Vmax XGT platform

Accessories

Trimmer head

Part No. 191D89-4

Cord/Line: 2.0mm x4m

Ref.: 96-M10L

Part No. 196324-1 Cord/Line: 2.4mm x3.6m







Part No. 197296-3

Cord/Line: 2.0mm x3m





Four-leaf Spiral Nylon cord

Size

Part No. 2.0mmx15m 197472-9 2.0mmx30m 197473-7 2.0mmx160m 197474-5 2.0mmx280m 197475-3

Size

Part No. 198501-1 2.4mmx15m 2.4mmx30m 198502-9

Plastic blade (255mm)

Plastic blade Set Part No. 198383-1

with nut M10x1.25 LH



Replacement plastic blade Part No. 198426-9

12pcs. set

Brushcutter blade 3-tooth blade

Blade dia.: 230mm Thickness: 3.0mm



4-tooth blade Part No. B-14118 Blade dia.: 230mm Thickness: 1.8mm



Protection guard for brush cutting blades

Exclusive Part No. 197294-7





Shoulder strap assembly

Comfort Part No.122906-3







UR003G





Charging Time Reference

40 Vinax	DC40RA FastCarging	DC40RC
BL4020 2.0Ah	22min	30 _{min}
*1 BL4025 2.5Ah	28 _{min}	38 _{min}
*1 BL4040 4.0Ah	45min	67min
*1 BL4050F 5.0Ah	50min	85 _{min}
*1 Recommended battery		

Constant Speed

Soft Start

Cordless Grass Trimmer

Wariable Speed **Brake** No Load Speed (RPM) Reversing

Electronic 3-Speed

Sound Power Level Sound Pressure Level Net weight

Metal Blade: 230 mm (9") Nylon Cutting Head: 350 mm (13-3/4") Plastic Blade: 255 mm (10") High / Mid / Low: 0 - 6,500 / 5,300 / 3,500 M10 x 1.25 LH

Nylon Cutting Head: 89.7 dB(A) Nylon Cutting Head: 72.2 dB(A) Vibration Level Left / Right: 2.5 / 2.5 m/s² or less
Dimensions (L x W x H) w/o Cutting Tool, w/ BL4020 / BL4025 / BL4040: 1735 x 355 x 230 mm (68-1/4 x 14 x 9") 4.1 - 4.7 kg (9.0 - 10.4 lbs.)

Standard Equipment: Safety Goggles, Metal Blade / Nylon Cutting Head / Plastic Blade (country-specific), Blade Cover (for the product with metal blade), Accessory Bag, Hex Wrench, Box Driver, Shoulder Belt, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sgWebsite: www.makita.com.sg Facebook: www.facebook.com/MakitaSG










DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



XGT

Cordless Grass Trimmer UR003G







High power as 25mL engine tool





Outer Rotor BL Motor provides high operating efficiency

Constant speed

Aluminum motor housing

Direct drive system

for more power, more speed and longer run time


High rotation speed

6,500 min⁻¹



Automatic torque Drive Technology

Automatically changes the cutting speed according to grass density.



AFT


Active Feedback sensing Technology

ששונונות

stator

rotor

Torque limiter turns the motor off if the tool is suddenly forced to lock



Multi functional control panel: near right hand position for easy access and operation



Electronic 3-speed

Reverse button / ADTMain power button

Operation mode can be selected to suit the type of blade.



Plastic blade mode

Nylon cord mode

Large push button main power switch allows for easy on/off even with gloved hand.

Work amount

on a single full battery charge about

290 m²

Battery: BL4050F

Work amount depends on the condition of battery, the type of grass, season, etc.

Run Time*

Nylon cutting head

...

High Med Low 45 / 80 / 259 min

With BL4050F

*on a single full battery charge / No load

Reverse switch



Reverse switch for clearing entangled weeds and grass from cutting head

Toolless handle lock mechanism for good portability







High water-resistance allows to operate the machine even if it is wet with water.



eXtreme Protection Technology

Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather

