



Cordless Pruning Saw

DUC101 100 mm (4")
UC100D 100 mm (4")



photo: DUC101

photo: UC100D

Charging Time

Fast Charging	12V ^{max} LITHIUM-ION			18V LITHIUM-ION				
	BL1016 1.5Ah 197393-5	BL1021B 2.0Ah 197396-9	BL1041B 4.0Ah 197406-2	BL1815N 1.5Ah 196449-1	BL1820B 2.0Ah 197254-9	BL1830B 3.0Ah 197599-5	BL1850B 5.0Ah 197280-8	BL1860B 6.0Ah 197422-4
DC10SB	22 min	30 min	60 min	15 min	24 min	22 min	45 min	55 min
DC10WD	50 min	70 min	130 min	30 min	45 min	60 min	110 min	130 min

Accessories

Holster set

Part No. 1911R0-4

Storage and carrying of the machine



Guide bar 4 set

Part No. 1910W0-3

Type: 80TXL
Length: 100 mm (4")
Gauge: 1.1 mm (0.043)



Saw chain 4 set

Part No. 1910V6-4

Type: 80TXL
Number of links: 26
Pitch: 0.325"
Gauge: 1.1 mm (0.043)

Cordless Pruning Saw

DUC101 100 mm (4")

	DUC101	UC100D
Brake	Guide bar length 100 mm (4") Type: 80TXL	100 mm (4") Type: 80TXL
Automatic Oiling	Saw chain Type: 80TXL Pitch: 0.325" Gauge: 1.1 mm (0.043)	Type: 80TXL Pitch: 0.325" Gauge: 1.1 mm (0.043)
	Chain speed 8.0 m/s (480 m/min) (1,570 FPM)	8.0 m/s (480 m/min) (1,570 FPM)
	Chain oil tank volume 55 mL (1.9 USoz)	55 mL (1.9 USoz)
	Vibration level Front: 4.6 m/s ² Rear: 4.0 m/s ²	Front: 4.8 m/s ² Rear: 4.1 m/s ²
	Dimensions (L x W x H) w/o Battery: 357 x 90 x 232 mm (14 x 3-1/2 x 9-1/8") w/ BL1815N / BL1820B: 394 x 90 x 245 mm (15-1/2 x 3-1/2 x 9-5/8") w/ BL1830B / BL1840B / BL1850B / BL1860B: 408 x 90 x 249 mm (16 x 3-1/2 x 9-3/4")	w/o Battery: 350 x 90 x 215 mm (13-3/4 x 3-1/2 x 8-1/2") w/ BL1016/BL1021B: 383 x 90 x 220 mm (15-1/8 x 3-1/2 x 8-5/8") w/ BL1041B: 398 x 90 x 226 mm (15-5/8 x 3-1/2 x 8-7/8")
	Net weight 1.6-2.0 kg (3.5-4.4 lbs.)	1.5-1.6 kg (3.3-3.5 lbs.)

Standard Equipment: Saw chain, Guide bar, Guide bar case, Round file (country-specific), Chain oil (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE

DUC101



Net weight
1.9 kg
Battery: BL1830B



UC100D



Net weight
1.5 kg
Battery: BL1021B





photo: DUC101



photo: DUC101

Movable guard

covers the upper side of guide bar, and opens gradually wider as saw chain cuts deeper in branch.

Lock-off lever accessible from both sides



Guide bar length
100 mm

Flexible rubber guard for hand

Work amount	
Test conditions: Cut ø50 cedar rod under an optimal pressing load of 20N or less on cutting edge. Saw chain: 80TXL	
DUC101 210 pcs. Battery: BL1830B	UC100D 73 pcs. Battery: BL1021B



Compact and lightweight BL motor



eXtreme Protection Technology

Automatic chain lubrication



minimizes the chance that saw chain will stall due to forgetting to supply chain oil.

New Tool-less change and tension adjustment of saw chain



- Simply loosen and re-tighten the lever to automatically adjust the tension of saw chain.
- This easy-to-operate large lever is designed to be pulled up and turned easily.