



Cordless Pruning Saw UC100D 100 mm (4")



Automatic chain
lubrication

Work amount

Test conditions:
Cut ø50 cedar rod under an
optimal pressing load of 20N
or less on cutting edge.
Saw chain: 80TXL

73 pcs.

Battery: BL1021B

Net weight

1.5 kg

Battery: BL1021B





Movable guard
covers the upper side of guide bar, and opens gradually wider as saw chain cuts deeper in branch.

Lock-off lever accessible from both sides



Guide bar length
100 mm

Flexible rubber guard for hand

Automatic chain lubrication



Oil tank cap

Chain oil view window

minimizes the chance that saw chain will stall due to forgetting to supply chain oil.

New Tool-less change and tension adjustment of saw chain



- Simply loosen and re-tighten the lever to automatically adjust the tension of saw chain.
- This easy-to-operate large lever is designed to be pulled up and turned easily.

Accessories

Holster set

Part No. 1911R0-4

Storage and carrying of the machine



Guide bar 4 set

Part No. 1910W0-3

Type: 80TXL
Length: 100 mm (4")
Gauge: 1.1 mm (0.043)






Saw chain 4 set

Part No. 1910V6-4

Type: 80TXL
Number of links: 26
Pitch: 0.325"
Gauge: 1.1 mm (0.043)





Charging Time

	 DC10SB	 DC10WD
 BL1016 1.5Ah 197393-5	22min	50min
BL1021B 2.0Ah 197396-9	30min	70min
BL1041B 4.0Ah 197406-2	60min	130min

Cordless Pruning Saw

UC100D 100 mm (4")

 Brake	Guide bar length	100 mm (4")
 Automatic Oiling	Saw chain	Type: 80TXL Pitch: 0.325" Gauge: 1.1 mm (0.043")
	Chain speed	8.0 m/s (480 m/min) (1,570 FPM)
	Chain oil tank volume	55 mL (1.9 USoz)
	Vibration level	Front: 4.8 m/s ² Rear: 4.1 m/s ²
	Dimensions (L x W x H)	w/o Battery: 350 x 90 x 215 mm (13-3/4 x 3-1/2 x 8-1/2") w/ BL1016/BL1021B: 383 x 90 x 220 mm (15-1/8 x 3-1/2 x 8-5/8") w/ BL1041B: 398 x 90 x 226 mm (15-5/8 x 3-1/2 x 8-7/8")
	Net weight	1.5-1.6 kg (3.3-3.5 lbs.)

Standard Equipment: Saw chain, Guide bar, Guide bar case, Round file (country-specific), Chain oil (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



 MakitaSG 



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE