









Run time*

77 min Battery: BL1830B

Strokes per minute

 $2,700 \, \text{min}^{-1}$

Net weight

3.0 kg
Battery: BL1860B
Model: DUH507







The performance to guide twig/branch towards blade tooth has been improved by:

- shortening the length covered by blunt extension
- tapering the tip of blunt extension

Blunt extension covers only 400mm from the front handle section.

Maximum branch diameter 15.0_{mm}



Chip receiver (option)


can make it easier for user to collect leaf and twig debris, thanks to:

- Lower height of the connecting levers
- Reduced step height of the edge of the chip catching plate















Model No.
DUH507
(500mm)

Model No.	Shear blade set	Blade cover	Chip receiver
DUH507 (500mm)	1911J1-6	458413-3	1910T1-0

Current

Highly durable crank mechanism

Increased crank wall thickness can:

- reduce the chance of falling off of the blade from the crank.
- · increase the contact area between the crank and blade, reducing wear of the crank.

Cordless Hedge Trimmer

Net weight

Easy-to-press front switch lever

Large main switch lever

for improved switch operation

Front switch lever has been redesigned to be easily pressed even when it is gripped at the





New

Charging Time

18V	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 _{min}	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min

DUH507	500 mm (19-3/4")	
Brake	Blade length	500 mm (19-3/4")
Diake	Max branch dia.	15 mm (9/16")
	Strokes per minute (SPM)	2,700
	Continuous use (min)	w/BL1830B: 77
	Vibration Level	Front/Rear: 1.1/0.6 m/s ²
	Sound Pressure Level	74 dB(A)
	Sound Power Level	85 dB(A)
	Dimensions (L x W x H)	w/o Battery: 872 x 209 x 188 mm
		(34-1/4 x 8-1/4 x 7-3/8")
		w/BL1815N/BL1820B: 909 x 209 x
		188 mm (35-3/4 x 8-1/4 x 7-3/8")
		w/BL1830B/BL1840B/BL1850B/
		BL1860B: 925 x 209 x 188 mm

(36-1/2 x 8-1/4 x 7-3/8") 2.7 - 3.0 kg (6.0 - 6.6 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproduct team@makita.com.sg

Website: www.makita.com.sg Facebook: www.facebook.com/MakitaSG





Standard Equipment: Blade cover, Battery, Charger

