



Cordless Circular Saw HS012G 165 mm (6-1/2")



40V Li-ion max



Max Cutting capacity

57 mm

Bevel angle: 0°

Work amount on a full battery charge BL4025

approx **110** cuts.

Test material: 50mm x 300mm Melapi

Lightweight

at **3.2** kg

with BL4025




Excellent combination of high power and lightweight design



Tool hanger



Metal guide for cutting line



Bevel range



Positive bevel stop
(at 22.5° and 45°)
(0° - right: 50°)

Twin LED Job light



with preglow and afterglow functions

Large lock-off lever



Magnesium diecast

Base plate, Safety cover and Blade case

Compact design

Predecessor Model: 170mm

HS012G: 157mm



Electric brake



eXtreme Protection Technology



Auto-start Wireless System



connects to compatible vacuum cleaners via Bluetooth.

Accessories

Specialized EFFICUT blade



Size (mm)	Part No.
165x 1.4 x 20 x 25T	B-63018

Guide rail adapter, Guide rail and Guide rail bag

Guide rail adapter Part No. 196953-0



Overall length (m)	Guide rail	Guide rail bag
	Part No.	Part No.
1	199140-0	E-05670
1.4	194368-5	E-05664
1.9	194925-9	E-10920
3	194367-7	E-10936

Clamp set




Part No. type A: 194385-5
type B: 199826-6

Bevel guide set



Adjustable angle of Guide rail
Part No. 196664-7

Guide rail Joint connector 2pc set



Part No. 198885-7(EU)

Charging Time

	Fast Charging DC40RA	DC40RC
*1 BL4020 2.0Ah 191L29-0	22 min	30 min
*1 BL4025 2.5Ah 191B36-3	28 min	38 min
*1 BL4040 4.0Ah 191B26-6	45 min	67 min
*1 BL4050F 5.0Ah 191L47-8	50 min	85 min
*1 BL4080F 8.0Ah 191X65-8	76 min	170 min

*1 Recommended battery

Cordless Circular Saw

HS012G 165 mm (6-1/2")

- Brake
- Constant Speed
- Soft Start
- Dust Collection
- Built-in Job Light

Wheel Diameter	165 mm (6-1/2")
Hole Diameter	20 mm (13/16")
Max Cutting Capacity	0°: 57 mm (2-1/4") 45°: 41 mm (1-5/8")
No Load Speed (RPM)	5,200
Vibration Level	2.5 m/s ² or less
Sound Pressure Level	91 dB(A)
Sound Power Level	102 dB(A)
Dimensions (L x W x H)	w/ Battery: 298 x 157 x 246 mm (11-3/4 x 6-3/16 x 9-11/16") w/ BL4020 / BL4025: 352 x 157 x 246 mm (13-7/8 x 6-3/16 x 9-11/16") w/ BL4040: 359 x 157 x 246 mm (14-9/64 x 6-3/16 x 9-11/16") w/ BL4050F: 388 x 157 x 246 mm (15-1/4 x 6-3/16 x 9-11/16") w/ BL4080F: 406 x 157 x 246 mm (16 x 6-3/16 x 9-11/16")
Net weight	3.2 - 4.4 kg (7.1 - 9.7 lbs.)

Standard Equipment: TCT saw blade, Hex wrench, Dust nozzle, Guide rule (country-specific), Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE