



Cordless Pruning Shears UP100D



■ Cordless Pruning Saw

DUC101



Net weight
1.9 kg
Battery: BL1830B



UC100D



Net weight
1.5 kg
Battery: BL1021B



■ Accessories

Shear blade U set

Part No. 1911W2-5

Replacement upper blade for Pruning shears



Shear blade L set

Part No. 1911W1-7

Replacement lower blade for Pruning shears



Dresser stone set

Part No. 1912E4-1

Dresser stone for Shear blade sharpening



Holster

Part No. 162C23-5



MAKPAC TYPE2

Part No. 821550-0

For smart organization and easy transportation of power tools and accessories



■ Charging Time

	Fast Charging	
	DC10SB	DC10WD
BL1016 1.5Ah 197393-5	22min	50min
BL1021B 2.0Ah 197396-9	30min	70min
BL1041B 4.0Ah 197406-2	60min	130min

Cordless Pruning Shears

UP100D

Capacity	Max cutting: 25 mm (1")
Vibration level	2.5 m/s ² or less
Sound pressure level	70 dB(A) or less
Dimensions (L x W x H)	w/o Battery: 259 x 53 x 98 mm (10-1/4 x 2-1/16 x 3-7/8") w/ BL1016/BL1021B: 285 x 64 x 98 mm (11-1/4 x 2-1/2 x 3-7/8") w/ BL1041B: 308 x 64 x 98 mm (12-1/8 x 2-1/2 x 3-7/8")
Net weight	0.89 - 1.1 kg (2.0 - 2.4 lbs.)

Standard Equipment : Oil supply, Wrench set, Whetstone, Holster

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE





Max cutting capacity
Ø25mm



Lightweight
0.89 kg
 with BL1016

12Vmax CXT BL Cordless Pruning Shears

Slim and Lightweight design

The use of BL Coreless motor*1 allows for reduction in the grip diameter and weight to reduce user's fatigue from pruning.

*1 BL motor without iron core on which copper coil wire is wound



Blade can be interlocked with the trigger, providing smooth blade movement similar to that of hand pruner.

Two control buttons on the tool body

Main power button and Blade opening angle adjustment button are located side by side on the rear of the grip for easier blade control.



Main power button
 Blade opening angle adjustment button

Adjustment of blade opening angle

The opening angle of the shear blades can be set in two levels.

fully open

Ø25mm



half-open

Ø18mm



Adjustment of blade overlap when closed



(by pressing and holding Blade opening angle adjustment button for 3 seconds or more when fully closed)



High cutting performance



with BL1021B

Work amount on a full battery charge

When cutting Ø15mm branches of Japanese cypress

about **2,200 pcs**



LED indicator

mounted on the front of the body, allowing the status of the machine to be checked at a glance.



Power on
 Blinking: Battery capacity warning (when the capacity is 20% or less)
 Solid on: Error indication (No battery capacity/ Thermal protection/ Overload)

External oil port

Lubrication oil can be injected without disassembling the blade.

