



Cordless Area Worklight ML010G 40Vmax, 18V, 14.4V / AC



XGT

40V^{Li-ion}max

18V^{Li-ion}
LITHIUM-ION

**Improved Self-righting
performance**



**Up to 4 batteries can be installed in
parallel.**

two LXT batteries + two XGT batteries



Continuous run time (approx)

Low mode **59 hours**

Battery: BL4080F x2 & BL1860B x2
all LEDs light up



Max luminous flux

5,500 lm



Compatible with 3 power sources



AC



two in parallel or one



two in parallel or one



Inlet type AC power supply cord


3 brightness settings

with memory function of the setting last time you power off




Low

1,500 lm



Medium

3,000 lm



High

5,500 lm

Lighting area selection



left
180°



360°



right
180°

Continuous run time (approx)

all LEDs light up

Battery	High	Medium	Low
BL1860B x2	4.5 h	8.5 h	16 h
BL4040 x2	6.5 h	11 h	21 h
BL4050F x2	8.5 h	14 h	27 h
BL4040 x2 + BL1860B x2	11 h	19.5 h	37 h
BL4050F x2 + BL1860B x2	13 h	22.5 h	43 h
BL4080F x2	13 h	23 h	43 h
BL4080F x2 + BL1860B x2	17.5 h	-	59 h

Battery capacity warning function




Hook for power cord



Battery fuel gauge



Padlock hole anti-battery theft



AC outlet allows for connecting up to 8 units of this light together.



IP54-rated water resistance (Only with DC power supply)



Diffusing lens
Daylight white
(approx 5,500K)

Carrying handle



Reflector
glows in the dark to help you locate the worklight body.

Charging Time

	Fast Charging				Fast Charging		
	DC18RC	DC18RD	DC18SD		DC40RA	DC40RB	DC40RC
BL1815N 1.5Ah 196449-1	15 min		30 min	BL4020 2.0Ah 191L29-0	22 min		30 min
BL1820B 2.0Ah 197254-9	24 min		45 min	BL4025 2.5Ah 191B36-3	28 min		38 min
BL1830B 3.0Ah 197599-5	22 min		60 min	BL4040 4.0Ah 191B26-6	45 min		67 min
BL1850B 5.0Ah 197280-8	45 min		110 min	BL4050F 5.0Ah 191L47-8	50 min		85 min
BL1860B 6.0Ah 197422-4	55 min		130 min	BL4080F 8.0Ah 191X65-8	76 min		170 min
							DC40WA
							260 min
							420 min

Not covered by EPTA-Procedure

Items of standard equipment and specifications may vary by country or area.

Cordless Area Worklight

ML010G 40Vmax, 18V, 14.4V / AC

Illuminance (High / Med. / Low)	at 1 m from the light source: 550 / 300 / 150 lx
Luminous flux	High / Med. / Low: 5,500 / 3,000 / 1,500 lm
Continuous run time on full battery charge	High / Med. / Low, w/ BL1860B x2: 4.5 / 8.5 / 16 hours High / Med. / Low, w/ BL4040 x2: 6.5 / 11 / 21 hours High / Med. / Low, w/ BL4050F x2: 8.5 / 14 / 27 hours High / Med. / Low, w/ BL4040 x2 & BL1860B x2: 11 / 19.5 / 37 hours High / Med. / Low, w/ BL4050F x2 & BL1860B x2: 13 / 22.5 / 43 hours High / Med. / Low, w/ BL4080F x2: 13 / 23 / 43 hours
Dimensions (L x W x H)	490 x 490 x 814 mm (19-1/4 x 19-1/4 x 32")
Net weight	14.4 - 19.2 kg (31.7 - 42.3 lbs.)
Power supply cord	2.5 m (8.2 ft)

Standard Equipment : AC power cord, Earth grounding plug

Battery & Charger Sold Separately

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



f MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE