



Max fastening torque

Fastening torque at 6 seconds after seating, when tightening M16 (grade 10.9) high strength bolt

# Max fastening torque: 200 N·m Fastening torque at 6 seconds after seating, when tightening M16 (grade 10.9) high strength bolt

#### Shoulder strap/Tool hanger

Allowing user to hang it on Shoulder strap as his/her support in high-place work or transfer from one work place to another.



Powered by 18V **Li-Ion G-battery** 

#### Belt clip can be attached.



Accessories **Shoulder strap** 

Part No. 197941-0

(with tool hanger)



**Tool hanger set** Part No. 197940-2

100 makita





ınkita

Belt clip set Part No. 195779-7

**Shoulder strap** 



#### Charging Time

18V Lithium-ion	DC18WA	DC18WB
<b>BL1815G</b> 1.5Ah	70 min	80 min
<b>BL1820G</b> 2.0Ah	90 min	105 min

## **Cordless Impact Wrench**

#### TW202D

Variable Speed

(RAKE) Brake

Reversing **≣**○ Built-in Job Light No load speed (RPM) Impacts per minute (IPM) Max fastening torque Sound pressure level

Square drive Capacity

Sound power level Vibration level

Dimensions (L x W x H)

w/o Battery: 176 x 79 x 191 mm (6-15/16 x 3-1/8 x 7-1/2") w/BL1820G: 176 x 79 x 223 mm (6-15/16 x 3-1/8 x 8-3/4")

Net weight 1.5 kg (3.3 lbs.)

Standard Equipment: Shoulder strap, Tool hanger, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.

### **Makita Singapore Pte Ltd**

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sg

Website: www.makita.com.sg Facebook: www.facebook.com/MakitaSG







12.7 mm (1/2") Standard bolt: M8 - M16 (5/16 - 5/8") High strength bolt: M8 - M12 (5/16 - 1/2") 0 - 2,300

200 N·m (1,770 in.lbs.) 95 dB (A)

106 dB (A)