



# Cordless Fan CF003G 40Vmax / 18V / AC



**XGT**  
**40V** LITHIUM-ION  
**max**

**18V**  
LITHIUM-ION

450 mm fan diameter



- Compatible with
- 40Vmax XGT Li-Ion battery
  - 18V LXT Li-Ion battery
  - AC (through AC adapter)



AC





Front fan cover has been redesigned to supply air widely around the appliance therefore, this model is suited for air blowing or ventilation in a large place such as factory, warehouse, etc.

Compatible with 40Vmax / 18V Li-Ion battery / AC



XGT battery and LXT battery can be installed simultaneously.

Stepless air flow volume setting



Dial-style air flow volume adjustment (38 - 120m<sup>3</sup>/min)

Can be mounted onto MAKPAC cart



Portability can be enhanced by mounting the appliance onto MAKPAC cart.

Manual angle adjustment of fan head



90° up/45° down with a locking knob

Automatic oscillation



Automatic oscillation angle adjustment: 60°, 90°, 120° left/right

Accessory case



Located on the front of the appliance for storing AC adapter, etc.

### Continuous use (approx)

on a full battery charge [at Max air speed]

Battery	Without oscillation	With oscillation
BL1860B	90 min	85 min
BL4040	115 min	110 min
BL4080F	230 min	220 min

Max air flow volume  
**120**  
m<sup>3</sup>/min

Max air speed\*  
**300**  
m/min  
\*Measured at 1.0 m away from the appliance



### Charging Time

40V LXT-ION max	Fast Charging		18V LITHIUM-ION	Fast Charging	
	DC40RA	DC40RC		DC18RC	DC18SD
BL4020 2.0Ah 191L29-0	22 min	30 min	BL1815N 1.5Ah 196449-1	15 min	30 min
BL4025 2.5Ah 191B36-3	28 min	38 min	BL1820B 2.0Ah 197254-9	24 min	45 min
BL4040 4.0Ah 191B26-6	45 min	67 min	BL1830B 3.0Ah 197599-5	22 min	60 min
BL4050F 5.0Ah 191L47-8	50 min	85 min	BL1850B 5.0Ah 197280-8	45 min	110 min
BL4080F 8.0Ah 191X65-8	76 min	170 min	BL1860B 6.0Ah 197422-4	55 min	130 min

not covered by EPTA-Procedure  
Items of standard equipment and specifications may vary by country or area.

### Cordless Fan

#### CF003G 40Vmax / 18V / AC

Variable Speed	Air velocity	96-300 m/min
	Air flow	38-120 m <sup>3</sup> /min
	Fan diameter	450 mm (17-3/4")
	Fan head angle adjustment	Up: 90° / Down: 45° Left: 90° / Right: 90°
	Automatic oscillation	Left: 60, 90, 120° Right: 60, 90, 120°
	Continuous use (min.) w/o oscillation	w/ BL4040: 115 / w/ BL4080F: 230 / w/ BL1860B: 90
	Continuous use (min.) w/ oscillation	w/ BL4040: 110 / w/ BL4080F: 220 / w/ BL1860B: 85
	Dimensions (L x W x H)	w/o Battery: 312 x 633 x 770 mm (12-1/4 x 25 x 30-1/4")
	Net weight	w/o Battery: 7.9 kg (17.4 lbs.)

Standard Equipment : AC adaptor

### Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



Facebook MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE