

**Shear Wrench series**

**6924N**  
M22 (7/8") / M24 (1") / SHTB22  
1,100 N-m  
AC



**DWT310**  
M16 (5/8") / M20 (3/4") / M22 (7/8")  
804 N-m  
18V x2



**Impact Wrench series**

**TW001G**  
3/4" (19 mm)  
1,800 N-m  
40V max



**TW007G**  
1/2" (12.7 mm)  
760 N-m  
40V max



**TW004G**  
1/2" (12.7 mm)  
350 N-m  
40V max



**DTW1001**  
3/4" (19 mm)  
1,050 N-m



**DTW700**  
1/2" (12.7 mm)  
700 N-m  
18V



**DTW300**  
1/2" (12.7 mm)  
330 N-m  
18V



**Accessories**

**Sleeve size reference table**

\* Type F (for HEXA TECH (GFD France))

\*\* for Chinese market



Bolt Size	Outer sleeve			Inner sleeve	
	Hex (mm)	L (mm)	Part No.	L (mm)	Part No.
M16	27	35	764362-7	36	764416-0
		36	764367-7	36	*764421-7
		81	764406-3	82	764356-2
		100	764406-3	100	764400-5
M20	32	37	764361-9	38	764417-8
		37	**196276-6	38	*764422-5
		37	764361-9	38	*764422-5
		83	764363-5	84	764357-0
		100	764408-9	100	764402-1

Bolt Size	Outer sleeve			Inner sleeve	
	Hex (mm)	L (mm)	Part No.	L (mm)	Part No.
M22, 7/8"	36	39	153909-6	39	764418-6
		39	153909-6	39	*764423-3
		85	764364-3	85	764352-0
		100	764410-2	100	764404-7
5/8"	1-1/16"	170	764365-1	170	764354-6
		35	764362-7	36	764420-9
3/4"	1-1/4"	37	764361-9	38	764419-4
		83	764363-5	84	764353-8
		168	764366-9	169	764355-4

**Charging Time**

Battery Model	Fast Charging	
	DC40RA	DC40RC
*BL4020 2.0Ah 191L29-0	22 min	30 min
*BL4025 2.5Ah 191B36-3	28 min	38 min
*BL4040/F 4.0Ah 191B26-6	45 min	67 min
*BL4050F 5.0Ah 191L47-8	50 min	85 min

\*1 Recommended battery

Cordless Shear Wrench	
WT001G M16 (5/8"), M20 (3/4"), M22 (7/8")	
Brake	Capacity High strength torque shear bolt (HTB): M16, M20, M22 (5/8, 3/4, 7/8") Super (high) strength torque shear bolt (SHTB): M16, M20 (5/8, 3/4")
Anti-restart function	No load speed 17min <sup>-1</sup> Max fastening torque 804 N-m (593 ft.lbs.) Sound pressure level 82 dB (A) Sound power level 90 dB (A) Vibration level 2.5 m/s <sup>2</sup> or less Dimensions w/ M22 Sleeve, w/ BL4020, BL4025: (L x W x H) 255 x 95 x 334 mm (10 x 3-3/4 x 13-1/8") w/ M22 Sleeve, w/ BL4050F: 289 x 95 x 360 mm (11-3/8 x 3-3/4 x 14-1/8") Net weight 5.2 - 5.9 kg (11.5 - 13.0 lbs.)
Standard Equipment : Screwdriver, Shoulder belt, Outer sleeve, Inner sleeve, Battery, Charger	

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.





## Lightweight design



Reduces the stress on user's body in such a tough application as upward tightening of nut under steel beam.

WT001G

**5.5 kg**

battery: BL4040



Predecessor Model

**7.1 kg**

battery: BL1860Bx2

\* Without Sleeve

**Large work amount**

Fastening capacity of M22 Torque shear bolt:

battery: BL4025

**Approx. 150 pcs**

battery: BL4040

**Approx. 250 pcs**

## Higher maneuverability


Max. Torque shear bolt capacity

**M22**

- High strength torque shear bolt (HTB): **M16, M20, M22**
- Super high strength torque shear bolt (SHTB): **M16, M20**
- A325 Torque shear bolt: **5/8, 3/4, 7/8"**
- A490 Torque shear bolt: **5/8, 3/4"**



Battery capacity warning lamp



**BL**  
MOTOR

High power with BL motor

Hook designed for use with shoulder belt to carry the tool

Shoulder belt (for transportation)



**Bolt-tip ejection lever**

enables easy ejection of removed bolt-tip left in the socket of the machine.



**XPT**

eXtreme Protection Technology

