

### ■ Lawn care/Grass care

**Cordless Scarifier** UV001G







































### Accessories

### Vertical cutter set

- 380mm Vertical cutter
- Mainly for cutting lawn roots

Part No. 1913J5-0





40 V ***********************************	Fast Charging DC40RA	DC40RC
<b>BL4020</b> 2.0Ah 191L29-0	22 min	30 min
*1 <b>BL4025</b> 2.5Ah 191B36-3	28 min	38 min
*1 <b>BL4040/F</b> 4.0Ah 191B26-6	45 min	67 min
*1 <b>BL4050F</b> 5.0Ah 191L47-8	50 min	85 min
*1 <b>BL4080F</b> 8.0Ah 191X65-8	76 min	170 min

<sup>\*1</sup> Recommended battery

### Thatching blade set

- 380mm Thatching blade
- Mainly for removing thatch

Part No. 1913J7-6





### **Cordless Scarifier**

### UV001G 380mm (15")

( Brake

Anti-restart function

Constant Speed

Working depth -12 mm (-15/32") to 5 mm (+3/16")
Continuous run time on full battery charge w/ BL4080F x2, Vertical cutter: 38 min w/ BL4080F x2, Thatching blade: 41 min w/ BL4080F x2, Vertical cutter: 500 m² w/ BL4080F x2, Thatching blade: 510 m²
No load speed (RPM) 3,200 No load speed (RPM) Grass catcher capacity Sound pressure level Measured sound power level

Guaranteed sound power level Dimensions (L x W x H)

60 (B)(H) 89 (B)(A) 2.5 m/s² or less 1,020-1,240 x 680 x 915-1,155 mm (40-1/4-48-3/4 x 26-3/4 x 36-45-1/2″) 18.7-23.8 kg (41.2-52.5 lbs.) nt: Vertical cutter, Thatching blade, Socket wrench, Grass catcher, Standard Equipm Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

### **Makita Singapore Pte Ltd**

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sg Website: www.makita.com.sg Facebook: www.facebook.com/MakitaSG









DOWNLOAD LEAFLET

86 dB(A)

PRINTED IN SINGAPORE

# Cordless Scarifier UV001G 380mm (15")









## Healthy Lawn Growth and Maintenance with Aeration & Thatching









XPT (eXtreme Protection Technology) / IPX4-compatible





### Powered by 40Vmax XGT Li-lon battery (two in parallel or one)



Automatic battery switching

If two batteries are installed and one battery in use has run out of power, the battery system automatically switches to the other one.

(No special operation, such as on/off operation, is required.)

### Actual mowing area on full battery charge





Thatching blade
Working depth: 0 mm

510 m<sup>2</sup>

### Stable operation due to the center of gravity located in the front

Heavy items, such as motor, battery and the lower section of handle, are located in the front of the machine body

This structure can minimize the chance that the front wheels will leave the ground, allowing for reliable power transmission to blade to provide consistent cutting depth.



Blade section



Lower section Blade s

### Toolless foldable handle

Handle can be folded in two steps for compact storage simply by loosening thumb screws without tool

