



Cordless Jig Saw JV002G



40V LITHIUM max




Cutting speed
20% up

Compared to predecessor 18V model



3 Orbital settings + Straight cutting



Optimum cutting action can be selected by simply turning the change lever.


Position	Cutting action	Applications
0	Straight line cutting	Cuts in mild steel, stainless steel and plastics Clean cuts in wood and plywood
I	Small orbital cutting	Cuts in mild steel, aluminum and hard wood
II	Medium orbital cutting	Cuts in wood and plywood Fast cuts in aluminum and mild steel
III	Large orbital cutting	Fast cuts in wood and plywood

Variable speed control by dial



Number	Workpiece
4 - 6	Wood
3 - 6	Mild steel
3 - 4	Stainless steel
3 - 6	Aluminum
1 - 4	Plastics

Toolless blade clamp



with a blade holder which allows for one-hand blade change

Constant Speed



Reduces chance of drop in cutting speed.

LED job light



(Twin LEDs with light up function during standby mode)

Light reduction function

- Less glare when cutting metal
- Press and hold the main power button for 3 brightness settings.
- Memory function: The tool remembers the job light brightness set last time and the light will light up at that brightness when turned on.

Dust Collection



Dust nozzle can be set to Base firmly with Thumb screw.

Dust nozzle can be attached over the sawdust exhaust port for connection to Makita vacuum cleaner.

SOFT NO-LOAD

New Soft no-load

- Easy, precise alignment of blade with pencil line at cut starting point
- With disabling function
- If the tool detects no-load motor rotation during intermittent operation such as precision cut-out, it switches automatically back to Soft no-load mode.

Bevel range

0 to 45° left and right.



Less wobbling

Improved stability during cutting due to a wider base plate

XPT

Extreme Protection Technology

Accessories

Dust nozzle assembly

For dust collection
Part No. 122C71-6



Anti-splintering device

Part No. 192557-6



Guide rule set

Part No. 193516-3



Guide rail adapter set

Part No. 193517-1
197252-3



Guide rail

Overall length:
1m, 1.4m, 1.5m,
1.9m, 3m



Charging Time

	Fast Charging DC40RA	DC40RC
*1BL4020 2.0Ah 191L29-0	22 min	30 min
*1BL4025 2.5Ah 191B36-3	28 min	38 min
*1BL4040/F 4.0Ah 1910N6-8	45 min	67 min

*1 Recommended battery

Cordless Jig Saw

JV002G

- Variable Speed
- Brake
- Anti-restart function
- Constant Speed
- Soft Start
- Orbital Cutting
- Bayonet Shank
- Dust Collection
- Toolless blade change
- Built-in Job Light

Capacity	Wood:	135 mm (5-5/16")
	Mild steel:	10 mm (3/8")
	Aluminum:	20 mm (13/16")
Stroke length		26 mm (1")
Strokes per minute (SPM)		0 - 3,500
Bevel range		0 - 45°
Vibration level		
Work mode: cutting sheet metal		4.2 m/s ²
Sound pressure level		88 dB (A)
Sound power level		96 dB (A)
Dimensions (L x W x H)		
w/ BL4020 / BL4025:		272 x 84 x 208 mm (10-3/4 x 3-5/16 x 8-3/16")
w/ BL4040 / F:		280 x 84 x 208 mm (11 x 3-5/16 x 8-3/16")
Net weight		2.7 - 3.0kg (6.0 - 6.6 lbs.)

Standard Equipment :

Jig saw blade, Cover plate, Dust nozzle (country-specific), Kert board, Hex wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE