

Lawn care/Grass care

Cordless Lawn Mower

LM001G (480mm)
LM002G (530mm)
40V max



LM003G (380mm)
LM004G (430mm)
40V max



Cordless Scarifier

UV001G (380mm)
40V max



Cordless Grass Trimmer

UR012G
40V max x2



Max Output
2.0 kW

Cordless Grass Trimmer

UR013G
40V max



UR008G
40V max



UR003G
40V max



UR017G
40V max



Max Output
1.5 kW

Max Output
1.0 kW

Max Output
0.55 kW

Max Output
0.6 kW

Cordless Multi Function Power Head

UX01G
40V max



Cordless Blower

UB001G
40V max



Max Output
1.0 kW

Accessories

Blade type	Model (size)	Applications and features
	LM003G (380mm)	<ul style="list-style-type: none"> Standard blade for both grass collection and mulching Features Improved grass collecting performance achieved by redesigning blade tips to increase air flow volume.
	LM004G (430mm)	
	LM003G (380mm)	<ul style="list-style-type: none"> Cuts grass clippings into small particles and scatters them evenly on the ground for mulching. Ensures proper air flow volume required for mixing grass clippings in the deck.
	LM004G (430mm)	

Mulching plug

Model: LM003G
Size: 380mm
Model: LM004G
Size: 430mm
Essential component for mulching



Charging Time

	DC40RA	DC40RC
*BL4020 2.0Ah 191L29-0	22 min	30 min
*BL4025 2.5Ah 191B36-3	28 min	38 min
*BL4040 4.0Ah 191B26-6	45 min	67 min
*BL4050F 5.0Ah 191L47-8	50 min	85 min
*BL4080F 8.0Ah 191X65-8	76 min	170 min

Cordless Lawn Mower			
LM003G / LM004G 380 mm (15") / 430 mm (17")			
	Brake	LM003G	LM004G
	Anti-restart function	LM003G	LM004G
	Cutting width	380 mm (15")	430 mm (17")
	Cutting height adjustment	Adjustment range: 20 - 75 mm (13/16 - 2-15/16")	Adjustment range: 20 - 75 mm (13/16 - 2-15/16")
	No load speed (RPM)	3,800	3,800
	Wheel diameter	140 / 165 mm (5-1/2 / 6-1/2")	140 / 165 mm (5-1/2 / 6-1/2")
	Actual mowing area on full battery charge	w/ BL4080F: 780 m ²	w/ BL4080F: 830 m ²
	Continuous run time on full battery charge	w/ BL4080F: 49 min	w/ BL4080F: 52 min
	Grass catcher capacity	40 L (1,353 oz)	50 L (1,691 oz)
	Vibration Level	2.5 m/s ² or less	2.5 m/s ² or less
	Measured sound power level	90 dB(A)	90 dB(A)
	Guaranteed sound power level	93 dB(A)	93 dB(A)
	Sound pressure level	83 dB(A)	81 dB(A)
	Dimensions (L x W x H)	During operation: 1,370 - 1,420 x 450 x 990 - 1,020 mm (54 - 56 x 17-3/4 x 39 - 40-1/4")	During operation: 1,390 - 1,440 x 460 x 990 - 1,020 mm (54-3/4 - 56-3/4 x 18-1/8 x 39 - 40-1/4")
	When stored (w/o Grass box):	520 x 450 x 880 mm (20-1/2 x 17-3/4 x 34-3/4")	520 x 460 x 885 mm (20-1/2 x 18-1/8 x 34-3/4")
	Net weight	14.9 - 17.3 kg (32.8 - 38.1 lbs.)	15.6 - 18.2 kg (34.4 - 40.1 lbs.)

Standard Equipment :
Socket wrench, Blade, Mulching plug, Grass catcher, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE



Continuous run time

LM003G	LM004G
49 min	52 min

Battery: BL4080F on a full battery charge

Powered by 40Vmax XGT Li-Ion battery



Mowing area


on a full battery charge (with BL4080F)

The results shown here are mowing area under actual load and continuous operation time (when the grass is cut from 50 to 30mm in height), which are approximate values when a fully charged battery is used; therefore, they depend to a great extent on grass density, cutting height, etc.

LM003G (380mm)



LM004G (430mm)



Continuous use

on a full battery charge (with BL4080F)

The results shown here are mowing area under actual load and continuous operation time (when the grass is cut from 50 to 30mm in height), which are approximate values when a fully charged battery is used; therefore, they depend to a great extent on grass density, cutting height, etc.

LM003G (380mm)

about
49 min

LM004G (430mm)

about
52 min

Higher mowing performance

The blade is designed to tilt down towards the front of the mower when attached, minimizing double-cutting to reduce the load on the machine for reduced energy consumption, better feeling of cutting and improved grass collecting performance.



Cutting, Collecting, Mulching*

*Mulching plug required.

Easy-to-operate handle lock levers

- each side of the handle can be locked/unlocked with just a single action without tool.
- allows for easier folding of handle when storing the mower.



Upright storage



Easier cutting height adjustment

- The increase/decrease directions have been reversed so that they can synchronize easier with the high/low directions of height adjustment in user's mind.
- Easy-to-grip egg-shaped lever top
- U-shaped notches, which provide positive stops for lever, can be visually checked, making it easy to adjust cutting height.



Less force required to turn on the mower

Reduction in user fatigue has been achieved by redesigning the shape of switch lever and the specification of spring to reduce the force required to pull switch lever to turn on the mower.



Pull force required to turn on the mower
Approx. 11 N

The inside of cutting deck can be washed.



XPT
eXtreme Protection Technology / IPX4-compatible

LM003G
380 mm (15")

Plastic Deck



LM004G
430 mm (17")

Plastic Deck

