



Cordless Bar Light ML012G / DML818



XGT
40V L⁺ION
max

18V
LITHIUM-ION



photo: ML012G



photo: ML012G



photo: DML818

Continuous use
on a full battery charge

ML012G

High / Medium / Low

4.5 / 9.5 / 20h

Battery: BL4025 / F

DML818

High / Medium / Low

4 / 9.5 / 19h

Battery: BL1850B

ML012G



DML818



Bar type light for wide area illumination

For wide area illumination, we use a long bar type light consisting of two LED light bars, each of which is covered with a light-diffusing plastic lens.



Max luminous flux
1,700 lm
with all 42 LEDs on

photo: ML012G

Foldable

- LED light bar section can be folded in half, allowing for double-sided illumination when folded.
- Compact for transportation or storage




Illuminating angle adjustment by rotating LED light bar

By rotating LED light bar clockwise maximum 90 degrees or counterclockwise maximum 180 degrees, user can adjust the illuminating angle to 7 angles.



Telescopic hook

- Clip on each end of Telescopic hook holds the LED light bar section securely.
- Telescopic hook allows user to attach the appliance to the hood, back door and more of vehicles, making it ideal for use as a worklight in automotive workshops.



Illuminating angle adjustment with Telescopic hook attached



Continuous use Illuminating with both lower and upper LED light bars (with all 42 LEDs on)

Model No. Battery	ML012G 40V max					DML818 18V					
	BL4020	BL4025/F	BL4040/F	BL4050F	BL4080F	BL1815N	BL1820B	BL1830B	BL1840B	BL1850B	BL1860B
Brightness setting											
High (1,700 lm)	3.5 h	4.5 h	7.0 h	8.5 h	14 h	1.3 h	1.7 h	2.4 h	3.0 h	4.0 h	5.0 h
Medium (800 lm)	7.5 h	9.5 h	15 h	19 h	31 h	2.8 h	3.5 h	5.0 h	7.0 h	9.5 h	11 h
Low (400 lm)	16 h	20 h	32 h	40 h	65 h	5.5 h	7.5 h	10 h	15 h	19 h	23 h



Top hook

This durable metal hook allows for use as a hanging worklight.

Hand strap

Supplied hand strap allows for use as a hanging worklight.




3 Strap holes



Main power / Brightness switch

High → Med → Low → OFF

Illumination mode selection switch



- 1 All 42 LEDs on
- 2 24 LEDs on LEDs of lower light bar only
- 3 18 LEDs on LEDs of upper light bar only



ML012G

DML818

Charging Time

Model No. Battery	Fast Charging DC40RA DC40RC		Model No. Battery	Fast Charging DC18RC DC18SD	
	22 min	30 min		15 min	30 min
BL4020 2.0Ah 191L29-0	22 min	30 min	BL1815N 1.5Ah 196449-1	15 min	30 min
BL4025 2.5Ah 191B36-3	28 min	38 min	BL1820B 2.0Ah 197254-9	24 min	45 min
BL4040 4.0Ah 191B26-6	45 min	67 min	BL1830B 3.0Ah 197599-5	22 min	60 min
BL4050F 5.0Ah 191L47-8	50 min	85 min	BL1850B 5.0Ah 197280-8	45 min	110 min
BL4080F 8.0Ah 191X65-8	76 min	170 min	BL1860B 6.0Ah 197422-4	55 min	130 min

Cordless Bar Light

ML012G / DML818

Color temperature	Daylight white: 5,000 K
Luminous flux	High / Med. / Low: 1,700 / 800 / 400 lm
Illuminance	at 0.5m from the light source, with all 42 LEDs on: High / Med. / Low: 2,000 / 1,000 / 450 lx
Continuous use	ML012G: w/ BL4040, High / Med. / Low: 7 / 15 / 32 hours DML818: w/ BL1860B, High / Med. / Low: 5 / 11 / 23 hours
Dimensions (L x W x H)	ML012G: w/o Battery: 972 x 85 x 100 mm (38-1/4 x 3-3/8 x 3-15/16") DML818: w/o Battery: 972 x 80 x 101 mm (38-1/4 x 3-1/8 x 4")
Mounting width of Telescopic hook	1,130 - 1,900 mm (44-1/2 - 74-3/4")
Net weight	ML012G: w/o Battery: 1.1 kg (2.4 lbs.) DML818: w/o Battery: 1.1 kg (2.4 lbs.)

Standard Equipment: Telescopic hook, Hand strap

not covered by EPTA-Procedure

Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE