

2024/25 (VERSION 2.0)

®

Makita



NEW LAUNCH

FEATURES / COMING SOON



EXPAND YOUR LITHIUM LINE UP

PP001G

Cordless Hole Puncher



Automatic punch return



- Equipped with the 40Vmax XGT Li-Ion battery
- High-efficiency punching with high-power BL motor
- Compatible with various steel materials (steel, stainless steel, channel steel, aluminum and copper)
- 360° rotatable motor section
- Return lever
- Punching up to a maximum plate thickness of 9mm and a hole diameter of \varnothing 20mm



PP001GZK Cordless Hole Puncher

New

40Vmax XGT BL Cordless Hole Puncher

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

Capacity	Steel: 20 mm Stainless steel: 20 mm
Dimensions (L x W x H)	w/ BL4020 / BL4025: 398 x 129 x 315 mm (15-5/8 x 5-1/8 x 12-3/8")
Net weight	11.6 - 12.8 kg (25.6 - 28.2 lbs.)



40Vmax XGT BL

1

Punch, Die, Grip, Bar for fastening nuts, Hex wrench, Wrench, Screw, Spanner
Z: Battery and Charger are sold separately

TW002G

Cordless Impact Wrench



- BL motor delivers 1,700 N·m (1,250 ft.lbs.) of max torque and 2,200 N·m (1,620 ft.lbs.) of nut-busting torque
- Electronic 4 stage impact power selection for added versatility
- 3 modes of reaction time for automatic stop available both in forward and reverse rotation modes
- Trigger switch with full speed mode allows for less hand and finger fatigue
- Style of socket retention: C ring



TW002GM201 (RM2J) / GZ

12.7mm (1/2") Cordless Impact Wrench

New

1,700 N·m (1,250 ft.lbs.) Impact Wrench, Reverse Rotation Auto Stop Mode

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

Square Drive	12.7 mm (1/2")
Max Fastening Torque	1,700 N·m (1,250 ft.lbs.)
Nut-busting torque	2,200 N·m (1,620 ft.lbs.)
No Load Speed (RPM)	Max / Hard / Med / Soft: 0 - 1,800 / 0 - 1,000 / 0 - 900 / 0 - 850 min ⁻¹
Impacts Per Minute (IPM)	Max / Hard / Med / Soft: 0 - 2,400 / 0 - 2,000 / 0 - 1,800 / 0 - 1,700 min ⁻¹
Dimensions (L x W x H)	w/ BL4025: 213 x 94 x 297 mm (8-3/8 x 3-11/16 x 11-3/4")
Net weight	3.9 - 5.1 kg (8.6 - 11.2 lbs.)



40Vmax XGT BL XPT

Belt clip, Battery, Charger, Hook, Z: Battery and Charger are sold separately

TW010G

Cordless Impact Wrench

Max. fastening torque
3,150 N·m
6 seconds after seating, when tightening

- Square drive D-handle impact wrench powered by a 40Vmax XGT Li-Ion battery
- An excellent combination of high torque and maneuverability
- Trigger switch with full speed mode
- Ring illumination LED
- For tightening large diameter bolts
- Auto-stop system available in both forward/reverse rotation modes



TW010GZ
25.4mm (1") Cordless Impact Wrench

New

40Vmax XGT BL Cordless 1" (25.4 mm) 3,150 N·m (2,320 ft.lbs.) Impact Wrench

Li-ion Ah	8.0	5.0	4.0	2.5	2.0
-----------	-----	-----	-----	-----	-----

Square Drive	25.4 mm (1")
Max fastening torque	3,150 N·m (2,323 ft.lbs.)
Fastening torque	Max/Hard / Med. / Soft: 2,850 / 1,600 / 1,000 / 600 N·m
Nut-busting torque	4,000 N·m (2,950 ft.lbs.)
Fastening capacities	Standard bolt: M27 - M45 High strength bolt: M20 - M33
No Load Speed (RPM)	0 - 1,200 / 0 - 850 / 0 - 700 / 0 - 600 min ⁻¹
Impacts per minute (IPM)	0 - 1,750 / 0 - 1,500 / 0 - 1,300 / 0 - 1,200
Dimensions (L x W x H)	w/BL4050F: 570 x 135 x 297 mm
Net weight	12.0 - 12.9 kg

40Vmax

Side handle, Tool hanger (Ring), Battery, Charger, Z: Battery and Charger are sold separately

PS001G

Cordless Polisher Scrubber

- 40Vmax XGT BL Cordless Polisher Scrubber
- Wobble suppression and Constant speed control
- Brush/Pad replacement without direct contact
- 3-speed settings
- Various brushes and pads are available to suit different applications.
- Adjustable and easy-to-grip handle design and Telescopic pipe adjustable with a lever



PS001GZ Cordless Polisher Scrubber

New

Wobble suppression and Constant speed control

Li-ion Ah	8.0	5.0	4.0	2.5	2.0
-----------	-----	-----	-----	-----	-----

No load speed	High / Med / Low: 600 / 350 / 150 min ⁻¹
Attachment size	Brush: 190 mm (7-1/2") Floor pad: 200 mm (7-7/8")
Telescopic pole	1,081 - 1,435 mm (42-1/2 - 56-1/2")
Continuous use	High / Med / Low: 30 / 50 / 140 min 189 mm (7-7/16")
Head height	1,081 - 1,435 x 204 x 361 mm (42-1/2 - 56-1/2 x 8 x 14-1/4")
Net weight	4.4 - 5.6 kg (9.7 - 12.3 lbs.)

40Vmax

Floor pad, Brush, Pad holder, Accessory bag, Splash guard, Battery, Charger, Z: Battery and Charger are sold separately

UC022G

Cordless Chain Saw



- Cutting performance and weight equivalent to or superior to 35mL class engine chainsaws
- High efficiency and lightweight design
- New lock-off mechanism
- New toolless tension adjustment of saw chain
- Excellent acceleration and Restartability (When Locked)
- Metal spike bumper firmly grips workpiece to provide more control, making cutting easier



UC022GZ 350mm (14") Cordless Chain Saw

New

40Vmax XGT BL Brushless Cordless 35 cm (14") Chain Saw

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

Guide Bar Length	350 mm (14")
Chain type	80T XL
Chain Pitch	0.325"
Chain Gauge	1.1 mm (0.043")
Chain Speed	0 - 25.5 m/s
Chain Oil Tank Volume	200 mL (6.8 US oz)
Dimensions (L x W x H)	w/o Guide bar, w/ BL4050F: 430 x 225 x 271 mm (17 x 8-7/8 x 10-5/8")
Net weight	5.1 - 5.4 kg (11.2 - 11.9 lbs.)



40Vmax



Guide bar, Saw chain, Guide bar case, Wrench, Round file, Chain oil, Battery, Charger, Chain cover, Glass laser visibility, Z: Battery and Charger are sold separately

UC029G

Cordless Pruning Saw

Work amount
415 pcs.
Battery: BL4025

Test conditions
Cut ø50 cypress wood under an optimal pressing load of 25N or less on the cutting edge



- Lightweight and compact body
- Tool-less change and tension adjustment of the saw chain
- Automatic chain lubrication minimizes the chance that saw chain will stall due to a lack of chain oil
- Chain oil view window allows operator to easily check oil level
- Lock-off lever accessible from both sides
- A hook with quick attachment/detachment (Optional accessory)



UC029GZ Cordless Pruning Saw

New

40Vmax XGT BL Cordless 150 mm (6") Pruning Saw

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

Guide bar length	150 mm (6")
Saw chain	Type: 80T XL Pitch: 0.325" Gauge: 1.1 mm (0.043")
Oil tank capacity	55 mL (1.9 oz)
Chain speed	8.0 m
Dimensions (L x W x H)	w/ BL4025: 474 x 95 x 255 mm (18-5/8 x 3-3/4 x 10")
Net weight	2.1 - 2.4 kg (4.6 - 5.3 lbs.)



40Vmax



Oil vessel set, Guide bar, Saw chain, Battery, Charger, File holder set, Chain cover
Z: Battery and Charger are sold separately

ML012G
Cordless Bar Light



DML818
Cordless Bar Light



- Bar type light for wide area illumination, 1,700 Lumens
- Supplied Telescopic hook allows user to attach the appliance to the hood, back door and more of vehicles, making it ideal for use in automotive industry
- LED light bar can be folded in half
- Rotating LED light bar clockwise 90 degrees or counterclockwise 180 degrees, user can adjust the lighting angle to 7 angles where click stop is provided
- Top hook and 3 strap holes for hanging use
- Press-button switch for High / Med / Low 3 brightness settings: 1,700 / 800 / 400 lumens
- 3 lighting mode selection with mode memory function
- Battery capacity warning function



ML012G Cordless Bar Light

New

40Vmax XGT Cordless Bar Light, 1,700 Lumens

Li-ion **8.0** 5.0 4.0 2.5 2.0

Color temperature	Daylight white: 5,000 K
Brightness setting	3
Luminous flux	High / Med. / Low: 1,700 / 800 / 400 lm w/ BL4040, High / Med. / Low: 7 / 15 / 32 hours at 0.5m from the light source, w/ all 42 LEDs on, High / Med. / Low: 2,000, 1,000, 450 lx at 1.0m from the light source, w/ all 42 LEDs on, High / Med. / Low: 600, 300, 100 lx w/o Battery:
Continuous use	High / Med. / Low: 7 / 15 / 32 hours at 0.5m from the light source, w/ all 42 LEDs on, High / Med. / Low: 2,000, 1,000, 450 lx at 1.0m from the light source, w/ all 42 LEDs on, High / Med. / Low: 600, 300, 100 lx w/o Battery:
illuminance	High / Med. / Low: 2,000, 1,000, 450 lx at 1.0m from the light source, w/ all 42 LEDs on, High / Med. / Low: 600, 300, 100 lx w/o Battery:
Dimensions (L x W x H)	972 x 85 x 100 mm
Net weight	2.0 kg (4.4 lbs.)



40Vmax **XGT XPT**

Telescopic hook, Shoulder strap, Battery and Charger are sold separately

DML818 Cordless Bar Light

New

14.4V/18V LXT Cordless Bar Light, 1,700 Lumens

Li-ion **6.0** 5.0 3.0 1.5

Color temperature	Daylight white: 5,000 K
Brightness setting	3
Luminous flux	High / Med. / Low: 1,700 / 800 / 400 lm w/ BL1860B, High / Med. / Low: 5 / 11 / 23 hours w/o Battery:
Continuous use	High / Med. / Low: 5 / 11 / 23 hours w/o Battery:
Dimensions (L x W x H)	972 x 80 x 101 mm (38-1/4 x 3-1/8 x 4")
Net weight	1.7 kg (3.7 lbs.)



18V 14.4V **LXT XPT**

Telescopic hook, Shoulder strap, Battery and Charger are sold separately

DTC102

Cordless Cable Cutter (Closed type)



DTC103

Cordless Cable Cutter (Closed type)



For cutting ACSR
(Aluminum
Conductors Steel
Reinforced).

DTC102ZK (Close Type)

Cordless Cable Cutter

New

Closed type for cutting Al / Cu cable

Li-ion Ah 6.0 | 5.0 | 3.0 | 1.5



Max blade opening width 65 mm (2-9/16")
Max cable cutting capacity Non-ferrous materials only (Al or Cu): 65 mm (2-9/16")
Dimensions (L x W x H) w/ BL1830B / BL1850B / BL1860B: 116 x 240 x 401 mm (4-9/16 x 9-1/2 x 15-3/4")
Net weight 3.5 kg (7.7 lbs.)

18V



Blade, Z: Battery and Charger are sold separately

DTC103ZK (Close Type)

Cordless Cable Cutter

New

Closed type for cutting ACSR (Aluminum Conductors Steel Reinforced)

Li-ion Ah 6.0 | 5.0 | 3.0 | 1.5



Max blade opening width 54 mm (2-1/8")
Max cable cutting capacity ACSR: Al 550mm² / ST 70mm²
Dimensions (L x W x H) w/ BL1830B / BL1850B / BL1860B: 116 x 240 x 401 mm (4-9/16 x 9-1/2 x 15-3/4")
Net weight 5.5 kg (12.1 lbs.)

18V



Blade, Z: Battery and Charger are sold separately

- 18V LXT Li-Ion Cordless Cable Cutter
- Developed specially for cutting only, allowing for lightweight design to provide excellent maneuverability
- Closed type
- DTC102 for cutting Al / Cu cable
- DTC103 for cutting ACSR (Aluminum Conductors Steel Reinforced)
- Automatic reverse function
- The blade opening angle can be adjusted to suit the diameter of the cable to be cut
- One LED job light with afterglow function
- Shoulder belt is provided as an optional accessory




Opening angle setting dial

6 stages
(ø10 - 50 mm)



LED job light

One LED with afterglow function



DTD173

Cordless Impact Driver



Max. fastening torque
180 N·m

High Power & Slim Head

Overall length
111 mm

- Compact and lightweight body with high power and maximum tightening torque of 180 N.m
- Can be used as a work light
- Offset battery backwards
- Slim head with no protrusion improves corner hitting performance in all directions
- New trigger switch
- Easy-to-see and use operation panel with "rear" placement



DTD173RTJ / Z Cordless Impact Driver

New

18V LXT BL Cordless Wood/Bolt/T-Mode 180 N-m (1,590 in.lbs.) Impact Driver

Li-ion Ah 6.0 | 5.0 | 3.0 | 1.5



Capacity-Machine screw	M4 - M8 (5/32" - 5/16")
Standard Bolt	M5 - M16 (3/16" - 5/8")
High Tensile Bolt	M5 - M14 (3/16" - 9/16")
Coarse thread (in length):	22 - 125 mm (7/8" - 4-7/8")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 3,600 / 0 - 3,200 / 0 - 2,100 / 0 - 1,100 min ⁻¹
Impacts Per Minute (IPM)	0 - 3,800 / 0 - 3,600 / 0 - 2,600 / 0 - 1,100 min ⁻¹
Fastening torque	Hard / Med. / Soft: 170 / 50 / 20 N·m
Max Fastening Torque	180 N·m (1,590 in.lbs.)
Dimensions (L x W x H)	111 x 81 x 234 mm
Net weight	1.5 kg (3.3 lbs.)

18V



LXT BL XPT

Hook, Hand strap, Phillips bit, Battery, Charger, Z: Battery and Charger are sold separately

UB003C

Battery Powered Blower



- High power BL Brushless and Lightweight design
- 3 Speed mode button
- Variable control trigger plus Cruise control lever
- High water-resistance compatible with XPT / IPX4
- Delivers up to 60 minutes of run time using PDC1500 with maximum speed mode
- Harness of Portable Power Pack can be attached and Nozzle reducing reaction force



UB003CZ Battery Powered Blower

New

Powerful blowing force (Max 24N)



Max Air Volume	w/ End nozzle, w/ PDC1500, Max speed mode: 17.6 m ³ /min
Max Air Velocity	w/ End nozzle, w/ PDC1500, Max speed mode: 86.0 m/s
Avg. Air Velocity	w/ End nozzle, w/ PDC1500, Max speed mode: 11.7 - 71.9 m/s
Blowing Force	w/ End nozzle, w/ PDC1500, Max speed mode: 0.7 - 24N
No Load Speed (RPM)	Mode1 / Mode2 / Mode3: 4,000-10,600 / 17,700 / 22,100 min ⁻¹
Dimensions (L x W x H)	w/ Nozzle: 913 - 1,013 x 178 x 298 mm
Net weight	2.8 - 3.1 kg (6.2 - 6.8 lbs.)



End nozzle, Band assembly

Recipro Saw Blade

Bi-Metal for Metal Cutting

- Has long life and excellent cost performance in cutting carbon steel
- Uses cost-effective Bi-Metal material for metal cutting
- Size: 150 mm, 225 mm
- Equipment suppliers and dismantlers
- 2pcs per package



Overall Length: 150mm
D-80298 (14 TPI)
D-80313 (18 TPI)
D-80335 (24 TPI)



Overall Length: 225mm
D-80307 (14 TPI)
D-80329 (18 TPI)
D-80341 (24 TPI)

Sleeve Chuck Bit Holder

Impact BLACK for E-form (NZ)

- By extending the bit, tightening screws and drilling work are available in deep places
- 1/4" Hex shank accessories are attachable
- Bits can be attached by simply pushing itself into the adapter
- Improved work efficiency in various workplaces
- For constructors, equipment dealers (plumber, wiring worker, etc.), sheet metal processor, metal worker, automobile maintenance shops, etc
- Three sizes are available to accommodate screw tightening and drilling in deep locations at optimum lengths



76mm (3") E-24941 (3")

152mm (6") E-24957 (6")

304mm (12") E-24963 (12")

IMPACT
Impact driver's accessory series
BLACK

Cut-Off Wheel

3mm Thickness

- Cut-Off Wheel for cutting metal and stainless steel
- Superiority in terms of performance and price over competitors (Supraflex products)
- Off-set shape allows intercutting and cutting
- Oil industries, Gus industries, General construction, Steel industry, Plumber, Shipbuilding industry, ect.
- 5pcs per package



D-79996
(100mm)

D-80014
(125mm)

D-80020
(180mm)

Trimmer Head

Bump & Feed (Flat type)

- A trimmer head with a flat bottom for improved work efficiency
- The quick loading mechanism allows you to load the nylon cord without disassembling
- The flat bottom makes it easy to trim grass while the trimmer head hitting the ground
- Grass can be cut lower as the spool is designed to be lower
- 100mm (4") M10X1.25LH



1914R8-6
(Nylon Dia. 2.0mm)

1914R6-0
(Nylon Dia. 2.4mm)

Makita®



**COMING
SOON**

Visit us at:
www.makita.com.sg



 @MakitaSG