



Cordless Circular Saw HS013G 415 mm (16-5/16")



XGT
40V **LI-ION**
max

Unveiling the world's largest 415 mm cordless circular saw*¹
Cuts through thick materials in a single stroke with high power similar to corded models

*¹ As of August 2024



Guide rule: optional accessory

Work amount

on a single full battery charge

Cut Melapi (Thickness: 150mm /
Width: 300mm / Bevel angle: 0° /
with BL4050F)

75 cuts



Comfortable cutting of thick materials with the high power similar to corded models




Lightweight design and enhanced maneuverability

The motor housing material has been changed from aluminum to resin, resulting in a weight reduction of 1.5kg compared with our AC model when a BL4050F battery is installed.

Lightweight
with BL4040
11.0 kg

Compact body

With the adoption of a BL motor, the width has been reduced by 65mm compared with our AC model, enhancing stability and maneuverability during blade changes.



AWS Auto-start Wireless System

The wireless activation function enables clean and comfortable operation. By connecting the tool to a vacuum cleaner, you can run the cleaner automatically along with the switch operation of the tool. Wireless unit is compatible with all supported tools.

XPT eXtreme Protection Technology

Enhanced Dust and Drip-proof Performance ensure reliable operation even under bad weather.

Protect stand (Part No. 4131E7-2)

(Standard equipment)
The resin stand allows for storage without damaging the tool.

Stabilizing the stand by pressing down the recessed portion with a foot allows for easy removal of the tool from storage.

The tool can be temporarily placed at an angle for easy access to the tool without bending over.

Accessories

TCT saw blade for circular saw

EFFICUT
415x35T
Part No. E-24832



Guide rule



Charging Time

	Fast Charging	
	DC40RA	DC40RC
BL4040 4.0Ah 191B26-6	45 min	67 min
*1 BL4040F 4.0Ah 191Q6-8	45 min	67 min
*1 BL4050F 5.0Ah 191L47-8	50 min	85 min
*1 BL4080F 8.0Ah 191X65-8	76 min	170 min

*1 Recommended battery

Cordless Circular Saw

HS013G 415 mm (16-5/16")

Soft Start	No load speed	2,100 min ⁻¹
Saw blade	Type: TCT saw blade / 35T, Diameter: 415 mm (16-5/16")	
Brake	Max cutting capacity	0°: 158 mm (6-1/4"), 45°: 106 mm (4-3/16")
Anti-restart function	Vibration level (EN62841-2-5)	Cutting wood: 2.5 m/s ² or less
Dust Collection	Vibration K Factor (EN62841-2-5)	Cutting wood: 1.5 m/s ²
	Sound pressure level (EN62841-2-5)	98 dB(A)
	Sound power level (EN62841-2-5)	106 dB(A)
	Noise K factor (EN62841-2-5)	3 dB(A)
	Dimensions (L x W x H)	606 x 233 x 476 mm (23-7/8 x 9-1/8 x 18-3/4")
	Net weight	11.0 - 12.0 kg (24.3 - 26.5 lbs.)
	Net weight (Battery)	BL4040 - BL4080F

Standard Equipment : TCT saw blade, Hex wrench, Joint, Protect stand, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE