



Cordless Brad Nailer DBN501



18Ga Brad Nailer



Brad Nail Capacity

Length: **15 - 50 mm**

Rapid firing capability

5.4 shots per second



Offers a similar feel to using a pneumatic nailer and excellent maneuverability

Rapid firing capability

Incorporating a pneumatic spring structure and driven by a BL motor, superior rapid firing capability has been achieved compared to competitors' models.



BL MOTOR

Bumper

Protects workpieces from scratches or damage.



Belt hook

Convenient for temporarily hanging the tool

LED job light



Main power switch

Indicator

Indicates remaining nail capacity

Slim nose

With an easy-to-aim ejection section for better visibility when driving nails

Window for checking remaining nail quantity

The magazine features a transparent part, enabling the quantity of remaining nails to be checked.



eXtreme Protection Technology

Tool-less nail jam clearing

Nails can be removed without tools in case of jamming



Anti-dry fire mechanism

Avoids dry firing by locking the contact arm when the remaining nails are 5 to 7.

Driving depth adjustment

For a wide variety of finish applications



Operation mode

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



Accessories

Brad nail

5,000pcs/box

Length	Part No.
15mm (5/8")	F-31867
20mm (3/4")	F-31870
25mm (1")	F-31883
30mm (1-3/16")	F-31896
32mm (1-1/4")	F-31902
35mm (1-3/8")	F-31915
38mm (1-1/2")	F-31928
40mm (1-9/16")	F-31931
45mm (1-3/4")	F-31944
50mm (2")	F-31957

Charging Time

	Fast Charging	
	DC18RC	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 min	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min

Cordless Brad Nailer

DBN501

Anti-restart function	Nail capacity	Length: 15 - 50 mm (9/16 - 2") Gauge: 18 Ga
Depth Adjustment	Magazine capacity	110 nails
Sequential and Bump-fire	Shot q'ty on a single full battery charge	1,700 pcs
Auto Firing Stop	(Battery)	BL1820B
Built-in Job Light	Vibration level (EN60745-2-16)	2.5 m/s ² or less
	Vibration K factor (EN60745-2-16)	1.5 m/s ²
	Sound pressure level (EN60745-2-16)	82 dB(A)
	Sound power level (EN60745-2-16)	93 dB(A)
	Noise K factor (EN60745-2-16)	3 dB(A)
	Dimensions (L x W x H)	246 x 96 x 301 mm (9-11/16 x 3-3/4 x 11-7/8")
Standard Equipment :	(Battery)	BL1820B
Nose adapter, Battery, Charger, Hook	Net weight	2.7 - 3.0 kg (6.0 - 6.6 lbs.)
	(Battery)	BL1815N - BL1860B

The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



[f MakitaSG](#)



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE