



# Cordless Finish Nailer DBN601 / DBN610



# 16Ga Finish Nailer



photo: DBN601



**DBN601**  
Straight type



**DBN610**  
Angled type



Finish Nail Capacity
Length: <b>19 - 64 mm</b>

Finish Nail Capacity
Length: <b>32 - 64 mm</b>



# Offers a similar feel to using a pneumatic nailer and excellent maneuverability

## Rapid firing capability

Incorporating a pneumatic spring structure and driven by a BL motor, superior rapid firing capability has been achieved compared to competitors' models.

**BL MOTOR**

### Bumper

Protects workpieces from scratches or damage.

**18V LITHIUM-ION**

### Belt hook

Convenient for temporarily hanging the tool

### Main power switch

### LED job light



photo: DBN601

### Slim nose

With an easy-to-aim ejection section for better visibility when driving nails

### Window for checking remaining nail quantity

The remaining nails can be checked.

**XPT**

**eXtreme Protection Technology**

## Tool-less jammed nail clearing

Nails can be removed without tools in case of jamming



## Anti-dry fire mechanism

Avoids dry firing by locking the contact arm when the remaining nails are 6 to 9.

## Driving depth adjustment

For a wide variety of finish applications



## Operation mode

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



## Accessories

**Finish nail** For model: DBN601  
2,000 pcs/box

Length	Part No.
25mm (1")	F-33922
30mm (1-3/16")	F-33935
32mm (1-1/4")	F-33948
35mm (1-3/8")	F-33951
38mm (1-1/2")	F-33964
40mm (1-9/16")	F-33977
45mm (1-3/4")	F-33980
50mm (2")	F-33993
57mm (1-1/4")	F-34001
60mm (2-3/8")	F-34014
64mm (2-1/2")	F-34027

## Charging Time

	Fast Charging	
	DC18RC	DC18SD
<b>BL1815N</b> 1.5Ah 196449-1	15 min	30 min
<b>BL1820B</b> 2.0Ah 197254-9	24 min	45 min
<b>BL1830B</b> 3.0Ah 197599-5	22 min	60 min
<b>BL1850B</b> 5.0Ah 197280-8	45 min	110 min
<b>BL1860B</b> 6.0Ah 197422-4	55 min	130 min

## Cordless Finish Nailer

### DBN601 / DBN610

Anti-restart function	Nail capacity	DBN601: Length: 19 - 64 mm (3/4 - 2-1/2") DBN610: Length: 32 - 64 mm (1-1/4 - 2-1/2")
Depth Adjustment	Magazine capacity	Gauge: 16 Ga 110 nails
Sequential and Bump-fire	Shot q'ty on a single full battery charge (Battery)	1,100 pcs
Auto Firing Stop	Vibration level (EN60745-2-16)	BL1820B 2.5 m/s <sup>2</sup> or less
Built-in Job Light	Vibration K factor (EN60745-2-16)	1.5 m/s <sup>2</sup>
	Sound pressure level (EN60745-2-16)	83 dB(A)
	Sound power level (EN60745-2-16)	94 dB(A)
	Noise K factor (EN60745-2-16)	3 dB(A)
	Dimensions (L x W x H)	DBN601: 276 x 98 x 320 mm (10-7/8 x 3-7/8 x 12-5/8") DBN610: 288 x 116 x 325 mm (11-3/8 x 4-9/16 x 12-3/4")
<b>Standard Equipment :</b>	(Battery)	BL1820B
Nose adapter, Battery, Charger, Hook	Net weight	DBN601: 2.9 - 3.3 kg (6.4 - 7.3 lbs.) DBN610: 3.0 - 3.3 kg (6.6 - 7.3 lbs.)
	(Battery)	BL1815N - BL1860B

The weight may differ depending on the attachment(s), including the battery cartridge.  
Items of standard equipment and specifications may vary by country or area.

## Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348  
Phone : +65-6546-8700 Fax : +65-6546-8711  
Email : msgproductteam@makita.com.sg  
Website : www.makita.com.sg  
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE