



High cutting efficiency with LXT 18V battery



Compact and lightweight



Powerful enough to perform smooth light duty cuts



Makes it easier to align with cutting lines.

Change lever for 3 orbital settings and straight cutting

Optimum cutting action can be selected simply by turning the lever.



Stroke length: 18mm

Blower function



Guide rail set

Length	Part No.
1.0m	199140-0
1.4m	194368-5
1.9m	194925-9
3.0m	194367-7



Position sheet set

Length	Part No.
1.9m	194910-2
3.0m	194419-4



Sheet 10000 set

Part No. 194416-0



makita


Soft grip

Powered by 18V LXT **Li-lon battery**

Connectable to a vacuum cleaner



Rigid aluminum base



Accessories

Support base set

- Reduces unstable tilting of the blade during bevel cuts, enabling stable cutting.
- Enhances the precision of curved cuts.

Part No. 1915R3-2





Guide rail adapter set

For use with guide rails

198704-7







Charging Time

18V LUTHUMHON	DC18RC	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 min	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min

Cordless Jig Saw

Rubber sheet 10000 set Part No. 194417-8

Push clamp set

Part No. 1913K5-7

DJV186

aw Blade

	Variab
١	(maxi) Brake
	Orbita
1	B Bayon Saw B
	Dust 0
1	
1	
	*EN62841-
in	Standard E

ariable Speed Orbital Cutting Bayonet Shank Jig Oust Collection

18 mm (11/16") 0 - 2,900 min⁻¹ Stroke length Strokes per minute Wood: 65 mm (2-9/16") Mild steel: 6 mm (1/4") Capacity Aluminum: 10 mm (3/8") 0 - 45 ° Cutting boards: 7.5 m/s², Bevel range Vibration level* Cutting sheet metal: 4.2 m/s² Cutting boards: 1.5 m/s², Vibration K factor* Cutting sheet metal: 1.5 m/s² 85 dB(A) Sound pressure level* Sound power level* Noise K factor * 93 dB(A) 93 dB(A) 3 dB(A) 241 - 257 x 81 x 196 mm (9-1/2 - 10-1/8 x 3-3/16 x 7-3/4") BLB182 - BL1860B 1.9 - 2.2 kg (4.2 - 4.9 lbs.) Dimensions (L x W x H) Battery Net weight Battery

lard Equipment: Jig saw blade, Hex wrench, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge The lightest and heaviest combination are shown in the table.

Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348 Phone: +65-6546-8700 Fax: +65-6546-8711 Email: msgproductteam@makita.com.sg Website: www.makita.com.sg

Facebook: www.facebook.com/MakitaSG







