

# Makita®

2025/26 (VERSION 2.0)



## NEW LAUNCH

FEATURES / COMING SOON



EXPAND YOUR LITHIUM LINE UP



# VC014GL

Cordless Vacuum Cleaner (Wet & Dry)



TANK CAPACITY  
FOR WET  
DEBRIS  
**4.5L**

## VC014GLZ Cordless Vacuum Cleaner

New

Cordless 7.5 L Dust Class L HEPA Portable Vacuum Cleaner (Wet & Dry)

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Capacity	Dry / Wet: 7.5 / 4.5 L
Continuous Use (min.)	w/ BL4050F: 22 - 120 min.
Air volume	1.0 - 2.0 m³/min
Max Sealed Suction	4.5 - 15 kPa
Suction Power	25 - 165 W
Dimensions (L x W x H)	400 x 251 x 282 mm (15-3/4 x 9-7/8 x 11-1/8")
Net weight	5.0 - 6.2 kg (11.0 - 13.7 lbs.)

40Vmax



Hose complete, Wide nozzle, Sash nozzle, Shoulder belt, Paper filter, Paper filter set, Wet filter, Battery, Charger, Z: Battery and Charger are sold separately

- Powered by a 40Vmax XGT Li-Ion battery
- 7.5 L Dust Class L HEPA Portable Vacuum Cleaner (Wet & Dry)
- Maximum suction power of 165 W (with a ø28mm x 2m flexible hose attached)
- Provides a runtime of up to 120 minutes with a BL4050F battery
- The tank capacity of 7.5 L for dry dust and 4.5 L for wet debris
- The HEPA filter effectively captures very fine particles



# JR003G

Cordless Recipro Saw



- Capable of cutting large-diameter pipe
- Delivers excellent cutting efficiency through the use of an XGT battery, a load-resistant BL motor, and enhanced stroke rate
- Enhanced structural rigidity around the crank mechanism
- Capable of cutting pipes with an outer diameter of up to 220 mm
- Adjustable stroke rate from 800 to 2,200 min<sup>-1</sup> with a dial improves cutting efficiency and extends blade life



## JR003GZ 26 mm (1") Cordless Recipro Saw

New

40Vmax XGT BL Cordless Recipro Saw, Chain Vise

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Max cutting diameter	ø220 mm (8-5/8")
Length of Stroke	26 mm (1")
Strokes Per Minut	0 - 2,200 min <sup>-1</sup>
Speed adjustment	800 - 2,200
Dimensions (L x W x H)	w/ BL4040: 583 x 103 x 152 mm (23 x 4-1/16 x 6")
Net weight	4.5 - 6.8 kg (9.9 - 15.0 lbs.)

40Vmax



Hex wrench, Hex socket head bolt, Recipro saw blade set for use with chain vise, Vise assembly, Front grip, Grip shaft, Battery, Charger, Blade, Z: Battery and Charger are sold separately



# HG001G

## Cordless Heat Gun



### HG001GZ02 Cordless Heat Gun

**New**

Max 600 degrees Celsius air temperature for a wide range of cordless works

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Air Temperature (°C)	Ambient temperature (blowing) - 600 °C (1,112.0 °F)
Air volume	120 / 150 / 180 / 200 L/min
Continuous use	w/ BL4040: 14 min.
Dimensions (L x W x H)	191 x 86 x 272 mm (7-1/2 x 3-3/8 x 10-3/4")
Net weight	1.5 - 2.7 kg (3.3 - 6.0 lbs.)

**40Vmax**


Reduction nozzle, Glass protection nozzle, Reflector nozzle, Wide slot nozzle, Battery, Charger, Z: Battery and Charger are sold separately

- A maximum temperature of 600°C and air volume of 200 L/min for fast PVC welding and efficient shrinking of thick cables
- LCD screen with backlight
- The quick-release mechanism allows tool-free nozzle removal without touching hot metal parts
- Memory and maximum temperature control functions
- Compatible with existing nozzles for our DC and AC models, offering greater versatility



# UC030G

## Cordless Chain Saw



Max. chain speed  
**29.0 m/s**

- Fast acceleration in response to trigger operation enables smooth, continuous cutting tasks like limbing
- Selectable chain speeds (ECO/Medium/High) with variable speed control by trigger and a mode memory function
- When excessive force is applied, the tool slows down, making it easy to adjust the load on the cutting edge
- IPX4M-rated for use in rainy conditions
- A shorter distance between the handle and hand guard



### UC030GZ 400, 450, 500mm (16, 18, 20") Cordless Chain Saw

**New**

40Vmax XGT BL Brushless Cordless Chain Saw

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Guide Bar Length	400, 450, 500 mm (16, 18, 20")
Chain Pitch	0.325"
Chain Gauge	1.3 / 1.6 mm (0.05 / 0.063")
Chain Speed	0 - 20.0, 24.5, 29.0 m/s
Chain Oil Tank Volume	260 mL (8.8 US oz)
Dimensions (L x W x H)	w/o Guide bar, Saw chain: 449 x 232 x 280 mm (17-3/4 x 9-1/8 x 11")
Net weight	BL4040F - BL4080F: 6.6 - 7.8 kg (14.6 - 17.2 lbs.)

**40Vmax**


XGT BL XPT



Guide bar, Saw chain, Guide bar case, Wrench, Chain oil, Round file, Battery, Charger, Z: Battery and Charger are sold separately

Items of standard equipment and specifications may vary by country or area. Net weight and dimensions may differ by the type of battery.





# GP001G

Cordless Grease Gun



## GP001GZ Cordless Grease Gun

New

40Vmax XGT, delivers up to 69 MPa (10,000 PSI) of max pressure

Li-ion Ah 5.0 | 4.0 | 2.5 | 2.0



Max operating pressure	69 MPa (10,000 PSI)
Flow rate	First speed: 145 mL/min (5.0 oz/min) Second speed: 220 mL/min (7.5 oz/min) Third speed: 290 mL/min (10.0 oz/min) Fourth speed: 350 mL/min (12.0 oz/min)
Grease capacity w/ Barrel A	Cartridge / Bulk: 410 / 455 g (14.5 / 16.0 oz)
Flexible hose length	1,200 mm (47-1/4")
Dimensions (L x W x H)	395 x 112 x 245 mm (15-1/2 x 4-3/8 x 9-5/8")
Net weight	5.1 - 6.5 kg (11.2 - 14.3 lbs.)

40Vmax



Shoulder Strap, Battery, Charger, Z: Battery and Charger are sold separately

- Stable discharge even under high-pressure operation
- Maintaining the same maximum discharge pressure of 69 MPa
- Air lock detection function
- Constant speed control for stable discharge operation
- Easier bellows cartridge replacement with an improved housing design
- Reduced air lock frequency during cartridge replacement by shortening the grease flow path



# GD001G / GD002G

Cordless Die Grinder



- 8 mm (1/4") Die Grinder
- Delivers high work efficiency and high durability.
- Equipped with a shaft lock, LED light, and other features for significantly improved usability compared with DGD800
- Ergonomically designed slim grip
- Active Feedback sensing Technology (AFT)
- High rotation speed: Deburring, grinding, Low rotation speed: Finish polishing, Removal of paint and rust



## GD001GZ / GD002GZ 8mm Cordless Die Grinder

New

40Vmax XGT Li-Ion Cordless 8 mm (1/4") Die Grinder

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



GD001GZ

Slide switch



GD002GZ

Paddle Switch

Capacity	Collet : 8 mm (5/16")
Wheel Diameter	52 mm (2-1/16")
No Load Speed (RPM)	7,000 - 29,000 min <sup>-1</sup>
Circumference of grip portion	146 mm (5-3/4")
Dimensions (L x W x H)	452 x 85 x 119 mm (17-3/4 x 3-3/8 x 4-11/16")
Net weight	2.2 - 3.4 kg (4.9 - 7.5 lbs.)

40Vmax



Wrench, Z: Battery and Charger are sold separately.



# GA056G

## Cordless Flat-head Angle Grinder

Tip access angle

# 39°

\* with 4 mm thick offset wheel

- Equipped with a newly designed tool-less wheel cover for flat-head angle grinders, allowing access at angles as small as 39°
- Paddle Switch, and using high voltage 40Vmax XGT Li-Ion battery and BL motor
- Delivering high operation efficiency even in work at recessed corners such as removal of weld marks on steel frame joints of narrow, acute angle
- Active Feedback sensing Technology (AFT) and Electric brake for maximum productivity



### GA056GZ 125mm (5") Cordless Flat-head Angle Grinder

**New**

Flat-Head Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

Wheel Diameter	125 mm (5")
Minimum access angle	39°
No Load Speed (RPM)	3,000 - 9,000 min <sup>-1</sup>
Cutting depth	30 mm (1-3/16")
Dimensions (L x W x H)	483 x 140 x 136 mm (19 x 5-1/2 x 5-3/8")
Net weight	3.1 - 4.4 kg (6.8 - 9.7 lbs.)



40Vmax



XGT BL AFT XPT

Side grip, Adapter, Lock nut wrench, Wheel cover for cut-off wheel, Battery, Charger, Z: Battery and Charger are sold separately

# TR001GZ

## Cordless Rebar Tying Tool



- Capable of tying a wide range of rebar sizes, from small to large diameters
- Dual BL motors for twisting and feeding ensure stable tying with 1.6 mm wire
- One-step wire reel loading is enabled by a linked cover and gear mechanism
- Tying strength - D10 x D10 rebar: approx. 300% increase, D22 x D22 rebar: approx. 200% increase



### TR001GZ Cordless Rebar Tying Tool

**New**

Capable of tying a wide range of rebar sizes, from small to large diameters

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

Tie Wire	Annealed wire: 16Ga (1.6 mm)
Applicable Rebars	D10 x D10 - (D16 x 2) x (D16 x 2)
Tying strength	D10 x D10: 305 % D22 x D22: 200 %
Nose width	5.6 mm (7/32")
Dimensions (L x W x H)	w/ BL4040: 375 x 113 x 331 mm (14-3/4 x 4-7/16 x 13")
Net weight	3.3 - 4.5 kg (7.3 - 9.9 lbs.)



40Vmax



Oil supply, Battery, Charger, Z: Battery and Charger are sold separately

Items of standard equipment and specifications may vary by country or area. Net weight and dimensions may differ by the type of battery.

**XGT** **LXT** **CXT**



# DTL302

Cordless Angle Impact Wrench



**DTL302Z 9.5mm (3/8") Cordless Angle Impact Wrench**

18V LXT, High torque is achieved by increasing hammer inertia

Li-ion Ah 6.0 5.0 3.0 1.5

**Max fastening torque** 310 - 340 N·m  
**Nut-busting torque** 500 - 530 N·m  
**Square drive** 9.5 mm (3/8")  
**No Load Speed (RPM)** Hard / Med. / Soft:  
0 - 3,200 / 0 - 1,500 / 0 - 1,000 min<sup>-1</sup>  
**Impacts Per Minute (IPM)** Hard / Med. / Soft:  
0 - 4,000 / 0 - 2,800 / 0 - 1,800 min<sup>-1</sup>  
**Head height** 78.0 mm (3-1/16")  
**Dimensions (L x W x H)** 396 - 414 x 80 x 86 - 92 mm (15-5/8 - 16-1/4 x 3-1/8 x 3-3/8 - 3-5/8")  
**Net weight** 1.8 - 2.1 kg (4.0 - 4.6 lbs.)

18V

Z: Battery and Charger are sold separately

**New**

- Developed targeted at work in tight spaces such as automobile and agricultural machinery maintenance
- Drive size: 9.5mm (3/8") Square, C ring (without hole)
- High torque is achieved by increasing hammer inertia, resulting in higher performance than competitors' models
- LED job light (3 stages brightness), Slim tool head, excellent maneuverability
- Equipped with an automatic impact stop system in forward/reverse rotation mode



## Offset Diamond Wheel

Masonry Works for 100mm (4") and 125mm (5") Grinder

- Improved cost performance compared to the current product (one star range)
- Three types of blades are available to meet a variety of user needs (Single, Double, Turbo)
- Features like SJS, SJS II, or Soft Start—these help reduce starting stress and protect the grinder's gearing
- Perfect for professional use on construction sites



### OFFSET DIAMOND WHEEL 100 X 16mm (4")

D-80547

D-80581

D-80628



Rough / SGL

Standard / DBL

Fine / Turbo

### OFFSET DIAMOND WHEEL 125 X 22.23mm (5")

D-80569

D-80606

D-80640



Rough / SGL

Standard / DBL

Fine / Turbo

Items of standard equipment and specifications may vary by country or area. Net weight and dimensions may differ by the type of battery.





**COMING  
SOON**

Visit us at:  
[www.makita.com.sg](http://www.makita.com.sg)



 MakitaSG