



Cordless Impact Driver
DTD201

High-speed, high-power for heavy-duty tasks



Max fastening torque

210 N·m

High-speed rotation

Max

3,700 min⁻¹



BL MOTOR XPT

Enhanced hammer and spring with increased motor speed deliver superior fastening performance to our previous model.

Work efficiency*

DTD201

160

Our 18V model 100

*Drove coach screws (lag screws) with a length of 90mm and a diameter of 9.0mm into melapi.



4-stage impact power selection + T-mode (for thin metal sheets only)

Four selectable speed settings make it easy to adjust the tool for a wide range of applications.



One-touch bit installation

Reduced resistance allows for easier bit installation.



Anti-bit wobbling structure

Ensures enhanced stability during fastening.

LED job light

Twin LEDs with preglow and afterglow functions



Variable speed control by trigger

Allows for speed adjustments based on the material or application.

Soft grip

Ergonomic rubberized soft grip for increased comfort



XPT
eXtreme Protection Technology



Charging Time

| | Fast Charging DC18RC | DC18SD |
|---------------------------------------|-------------------------|----------------|
| * ¹ BL1815N 1.5Ah 196449-1 | 15 min | 30 min |
| * ¹ BL1820B 2.0Ah 197254-9 | 24 min | 45 min |
| * ¹ BL1830B 3.0Ah 197599-5 | 22 min | 60 min |
| * ¹ BL1850B 5.0Ah 197280-8 | 45 min | 110 min |
| * ¹ BL1860B 6.0Ah 197422-4 | 55 min | 130 min |
| BL1890 9.0Ah 1915H4-0 | 85min | 200 min |
| BL18120 12.0Ah 1915J2-8 | 120min | 265 min |

Accessories

Tool hanger set

Part No. 191K57-9



Hook set

Part No. 194654-4



Battery protector set

Part No. 194649-7



Cordless Impact Driver

DTD201

| | | | |
|--|--------------------|------------------------|---|
| | Variable Speed | Capacity | Steel: 22 mm (7/8") / Wood (Auger bit): 24 mm (15/16") |
| | Brake | Max fastening torque | 210 N·m (1,860 in.lbs.) |
| | Reversing | No load speed | Max / Hard / Med. / Soft: 0 - 3,700 / 0 - 3,200 / 0 - 2,100 / 0 - 1,100 min ⁻¹ |
| | Electronic 4-Speed | Impacts per minute | Max / Hard / Med. / Soft: 0 - 4,400 / 0 - 4,200 / 0 - 3,600 / 0 - 2,000 min ⁻¹ |
| | Built-in Job Light | Vibration level | 9.9 m/s ² (EN62841-2-2, Mode: impact tightening with max. capacity) |
| | | Vibration K factor | 1.5 m/s ² (EN62841-2-2, Mode: impact tightening with max. capacity) |
| | | Sound pressure level | 97 dB (A) (EN62841-2-2) |
| | | Sound power level | 105 dB (A) (EN62841-2-2) |
| | | Noise K factor | 3 dB (A) (EN62841-2-2) |
| | | Dimensions (L x W x H) | 121 x 81 x 246 mm (4-3/4 x 3-3/16 x 9-11/16") |
| | | (Battery) | BL1860B |
| | | Net weight | 1.3 - 2.3 kg (2.9 - 5.1 lbs.) |
| | | (Battery) | BL1815N - BL18120 |
| | | Standard Equipment: | Hook, Hand strap, Battery, Charger |

The net weight value includes the lightest and heaviest combination of the attachment(s) for normal and safe use and battery cartridge(s) which are specified in the instruction manual.

Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE