



Cordless Finish Nailer DBN610



16Ga Finish Nailer



DBN610
Angled type

Finish Nail Capacity

Length:
32 - 64 mm



Offers a similar feel to using a pneumatic nailer and excellent maneuverability



Rapid firing capability

Incorporating a pneumatic spring structure and driven by a BL motor, superior rapid firing capability has been achieved compared to competitors' models.

BL MOTOR



Bumper

Protects workpieces from scratches or damage.




Belt hook

Convenient for temporarily hanging the tool

Main power switch

LED job light



DBN610

Slim nose

With an easy-to-aim ejection section for better visibility when driving nails

Window for checking remaining nail quantity

The remaining nails can be checked.



eXtreme Protection Technology

Tool-less jammed nail clearing

Nails can be removed without tools in case of jamming



Anti-dry fire mechanism

Avoids dry firing by locking the contact arm when the remaining nails are 6 to 9.

Driving depth adjustment

For a wide variety of finish applications



Operation mode

Selectable from Full sequential actuation mode (for single nailing) / Contact actuation mode (for continuous nailing)



Accessories

Finish nail For model: DBN601
2,000 pcs/box

Length	Part No.
25mm (1")	F-33922
30mm (1-3/16")	F-33935
32mm (1-1/4")	F-33948
35mm (1-3/8")	F-33951
38mm (1-1/2")	F-33964
40mm (1-9/16")	F-33977
45mm (1-3/4")	F-33980
50mm (2")	F-33993
57mm (1-1/4")	F-34001
60mm (2-3/8")	F-34014
64mm (2-1/2")	F-34027

Charging Time

	Fast Charging	
	DC18RC	DC18SD
BL1815N 1.5Ah 196449-1	15 min	30 min
BL1820B 2.0Ah 197254-9	24 min	45 min
BL1830B 3.0Ah 197599-5	22 min	60 min
BL1850B 5.0Ah 197280-8	45 min	110 min
BL1860B 6.0Ah 197422-4	55 min	130 min

Cordless Finish Nailer

DBN610

Anti-restart function	Nail capacity	Length: 32 - 64 mm (1-1/4" - 2-1/2") Gauge: 16 Ga
Depth Adjustment	Magazine capacity	110 nails
Sequential and Bump-fire	Shot q'ty on a single full battery charge (Battery)	1,100 pcs
Auto Firing Stop	Vibration level (EN60745-2-16)	BL1820B 2.5 m/s ² or less
Built-in Job Light	Vibration K factor (EN60745-2-16)	1.5 m/s ²
	Sound pressure level (EN60745-2-16)	83 dB(A)
	Sound power level (EN60745-2-16)	94 dB(A)
	Noise K factor (EN60745-2-16)	3 dB(A)
	Dimensions (L x W x H)	288 x 116 x 325 mm (11-3/8 x 4-9/16 x 12-3/4")
	(Battery)	BL1820B
	Net weight	3.0 - 3.3 kg (6.6 - 7.3 lbs.) BL1815N - BL1860B
Standard Equipment :		
Nose adapter, Battery, Charger, Hook		

The weight may differ depending on the attachment(s), including the battery cartridge.
Items of standard equipment and specifications may vary by country or area.

Makita Singapore Pte Ltd

7, Changi South Street 3, Singapore 486348
Phone : +65-6546-8700 Fax : +65-6546-8711
Email : msgproductteam@makita.com.sg
Website : www.makita.com.sg
Facebook : www.facebook.com/MakitaSG



MakitaSG



VISIT OUR WEBSITE



DOWNLOAD LEAFLET

PRINTED IN SINGAPORE