

XGT **LXT** **CXT**

2026/27 (VERSION 1.0)

Makita®



NEW LAUNCH

FEATURES / COMING SOON

TW009G

Cordless Impact Wrench



- D-handle impact wrench powered by a 40Vmax XGT Li-Ion battery
- An excellent combination of high torque and maneuverability
- 25.4 mm (1") square-drive & Tool-less 360° side-handle
- Ring illumination LED
- For tightening large diameter bolts
- Auto-stop system available in both forward/reverse rotation modes



TW009GZ 25.4mm (1") Cordless Impact Wrench

New

40Vmax XGT BL Cordless 1" (25.4 mm) 3,150 N·m (2,320 ft.lbs.) Impact Wrench

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Shank/Drive	Square Drive 25.4 mm (1")
Square Drive	25.4 mm (1")
Max fastening torque	3,150 N·m (2,323 ft.lbs.)
Fastening capacities	Standard bolt: M27 - M45 High strength bolt: M20 - M33
Fastening torque	2,850 / 1,600 / 1,000 / 600 N·m
No Load Speed (RPM)	0 - 1,200 / 0 - 850 / 0 - 700 / 0 - 600 min ⁻¹
Impacts per minute (IPM)	0 - 1,750 / 0 - 1,500 / 0 - 1,300 / 0 - 1,200
Dimensions (L x W x H)	w/ BL4050F: 435 x 135 x 297 mm
Net weight	10.8 - 11.8 kg

40Vmax

XGT BL AFT AWS AVT XPT

Side handle, Tool hanger (Ring), Battery, Charger, Z: Battery and Charger are sold separately

HR011G

Cordless Combination Hammer



HR011GM202 / GZ

28mm (1-1/8") Cordless Combination Hammer

New

40Vmax XGT BL AFT AWS AVT Cordless 28mm (1-1/8") Combination Hammer, SDS-PLUS

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0

HR011GM202 / GZ



Impact Energy Capacity	3.3 J Concrete / Steel / Wood / Core Bit / Diamond Core Bit (Dry Type): 28 / 13 / 32 / 68 / 80 mm
Blows Per Minute (BPM)	0 - 5,000 min ⁻¹
No Load Speed (RPM)	0 - 1,130 min ⁻¹
Dimensions (L x W x H)	w/ BL4040/BL4040F: 391 x 104 x 223 mm (15-3/8 x 4-1/8 x 8-3/4")
Net weight	3.8 - 5.5 kg (8.4 - 12.1 lbs.)

40Vmax

XGT BL AFT AWS AVT XPT

Side grip, Depth gauge, Grease vessel, Drill chuck assembly, Battery, Charger, Z: Battery and Charger are sold separately

- 28mm (1-1/8") SDS-plus
- Delivers an impact energy of 3.3 J
- Anti-Vibration Technology (AVT)
- Auto-start Wireless System (AWS) enables control via Bluetooth for on-demand dust extraction
- Three operation modes: Rotation only, Hammering with rotation, and Hammering only
- Twin-LED job light with preglow and afterglow functions



SC001G

Cordless Steel Rod Cutter



SC001GZK Cordless Steel Rod Cutter

New

40Vmax XGT BL Brushless Cordless 16 mm (5/8") Steel Rod Cutter

Li-ion Ah 8.0 5.0 4.0 2.5 2.0



Cutting capacity	Dia.: 3 - 16 mm
Cutting speed (sec)	1.7
Possible number of cuts	(ø16mm rebar): 250
Dimensions (L x W x H)	w/ BL4020 / BL4025: 321 x 103 x 285 mm (12-5/8 x 4-1/16 x 11-1/4")
Net weight	6.0 - 7.2 kg (13.2 - 15.9 lbs.)

40Vmax



Hex wrench, Wrench, Z: Battery and Charger are sold separately

- 40Vmax XGT BL Cordless 16 mm (5/8"), cutting speed has increased by approx. 65% compared to our 18V LXT model
- The tool can cut a ø16mm rebar in approx. 1.7 seconds, improving on-site efficiency and reducing construction time
- 0.9 kg lighter and 39 mm shorter than our 18V LXT model for easy portability
- Anti-scattering protector and 360° rotatable head for flexible positioning on-site



TD004G

Cordless Impact Driver



- With a maximum fastening torque of 230 N·m
- 4-stage impact power selection and T-mode (for thin metal sheets only) to match the type of screw and material
- One-touch bit installation for easy and quick bit changes
- Twin LED lights with preglow and afterglow functions for better illumination
- Equipped with an electric brake and anti-restart function
- Reversing switch is conveniently located



TD004GZ Cordless Impact Driver

New

High Power 230 N·m

Li-ion Ah 8.0 5.0 4.0 2.5 2.0



Capacity	Steel: 22 mm (7/8") Wood (Auger bit): 24 mm (15/16") 635 mm (1/4")
Hex Shank	635 mm (1/4")
Max fastening torque	230 N·m (2,040 in.lbs.)
No load speed	Max / Hard / Med. / Soft: 0 - 3,900 / 0 - 3,000 / 0 - 2,100 / 0 - 1,200 min ⁻¹
Impacts per minute	Max / Hard / Med. / Soft: 0 - 3,900 / 0 - 3,600 / 0 - 3,100 / 0 - 1,900 min ⁻¹
Dimensions (L x W x H)	136 x 86 x 248 mm (5-3/8 x 3-3/8 x 9-3/4")
Net weight	1.8 - 3.1 kg (4.0 - 6.8 lbs.)

40Vmax



Battery, Charger, Hook, Hand strap, Z: Battery and Charger are sold separately

LH001G

Cordless Table Top Miter Saw



LH001GZ 260mm (10-1/4") Cordless Table Top Miter Saw

New

Miter saw and Table saw in one tool with cordless convenience

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Wheel Diameter	255, 260 mm (10, 10-1/4")
Miter Angle	45° L / 52° R
Bevel Angle	0° - Left : 45°
Max Cutting Capacity (Bevel / Miter)	0° / 0°: 69 x 130 mm, 93 x 95 mm 0° / 45°LR: 69 x 85 mm, 93 x 67 mm 45°L / 0°: 35 x 130 mm, 53 x 95 mm 45°L / 45°L: 35 x 65 mm, 49 x 42 mm 45°L / 45°R: 35 x 91 mm, 49 x 67 mm
No Load Speed (RPM)	4,300 min ⁻¹
Dimensions (L x W x H)	545 x 476 x 585 mm
Net Weight	14.8 - 16.0 kg

40Vmax



XGT BL AWS

Battery, Charger, Z: Battery and Charger are sold separately

- 260mm (10-1/4") cordless table top miter saw powered by a 40Vmax XGT Li-Ion battery
- This model works not only as a cordless miter saw but also using its top table and rip fence, as a cordless table saw—delivering two tools in one
- Miter capacity of 45° left and 52° right, with positive stops at 0°, 15°, 22.5°, 30°, and 45°
- LED job light with cut line guide, Table height adjustment and Auto-start Wireless System



VL001G

Cordless Screed



- Powerful, stable vibration with 11,000 VPM
- Designed to reduce operator fatigue and strain
- The tool delivers stable concrete finishing and tamping with constant speed control
- Compatible with Portable Power Packs for extended runtime, PDC1200: 1,200 min. / BL4040F: 150 min
- 3 blade lengths are available: 900 mm/1,400 mm/1,800 mm
- Long rubber grip



VL001GZ Cordless Screed

New

Designed for concrete finishing and tamping applications

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Leveling width	900 / 1,400 / 1,800 mm (35-1/2 / 55 / 71")
Vibrations per minute	11,000 min ⁻¹
Continuous use	w/BL4040F: 150 min.
Dimensions (L x W x H)	1,562 x 935 / 1,435 / 1,836 x 258 mm (61-1/2 x 36-3/4 / 56-1/2 / 72-1/4 x 10-1/8")
Dimensions (Attachment)	Blade:
Net weight	900 / 1400 / 1800 mm 5.2 / 5.6 / 6.1 kg (11.5 / 12.3 / 13.4 lbs.)

40Vmax



XGT BL XPT

1

Blade cover, Hex wrench, Z: Battery and Charger are sold separately

BS002G

Cordless Pipe Belt Sander

High-efficiency
grinding
Belt speed:

13.5 m/s

(Dial 5)

- Constant speed control for stable grinding, polishing, and finishing operations
- Delivers high work efficiency with an XGT battery and a brushless motor, offering a wide range of belt speeds
- Variable speed control by dial for smooth polishing at low speeds and rust and paint removal at high speeds
- Maximum diameter of metal pipes for grinding: $\phi 125$ mm (5")
- 40 x 760 mm (1-9/16" x 30")



BS002GZ Cordless Pipe Belt Sander

New

40 x 760 mm (1-9/16" x 30") Cordless Variable Speed Pipe Belt Sander

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Belt Width	40 mm (1-9/16")
Belt Length	760 mm (30")
Belt Speed	3.1 - 13.5 m/s
Dimensions (L x W x H)	w/ BL4040F: 592 x 198 x 359 mm (23-1/4 x 7-3/4 x 14-1/8")
Net weight	4.2 kg (9.3 lbs.)

40Vmax



XGT LXT CXI

Abrasive belt, Grip, Battery, Charger, Z: Battery and Charger are sold separately

ML014G

Cordless Tower Light



ML014G Cordless Tower Light

New

40Vmax XGT/18V LXT Li-ion Cordless Tower Light, 15,000 Lumens

Li-ion Ah 8.0 | 5.0 | 4.0 | 2.5 | 2.0



Run Time (hrs)	w/ BL4080F: 2.0 - 28 h
Illuminance	at 1m from the light source: 400 - 5,000 lx at 5m from the light source: 16 - 200 lx
Luminous Flux	1,100 - 15,000 lm
Light angle adjustment	Light base: 180° Vertical Each light head: 180° Vertical, 180° Horizontal
Max setup height	2,430 mm (8 ft)
Dimensions (L x W x H)	Extended position: 780 x 680 x 1,085 - 2,430 mm
Net weight	12.8 kg (28.2 lbs.)

40Vmax 18V

XGT LXT

Shoulder belt, Z: Battery and Charger are sold separately

- Up to two batteries can be installed, only one XGT or 18V LXT
- Max luminous flux: 15,000 lm
- Stepless brightness settings: 15,000 lumens - 1,100 lumens
- 3.6 / 48 hours of continuous illumination with BL4080F+BL18120 batteries
- 3 Light heads rotate 180° horizontally and vertically, light base rotates 180° vertically
- Height of light head can be adjusted from 1,085 to 2,430mm



UG001G

Cordless Ground Trimmer



- T-shaped hedge-trimmer-type shear blades set at 90° to the shaft
- A 500 mm cutting width delivers high work efficiency
- Tool-less wheel position adjustment to suit the user's height
- 258 mm wheel spacing delivers straight-line stability
- Foldable handle reduces overall size for compact storage and easy transport
- Larger-diameter, wider front wheels



UG001GZ Cordless Ground Trimmer

New

40Vmax XGT Brushless 500 mm (19-3/4") Cordless Ground Trimmer

Li-ion Ah 8.0 5.0 4.0 2.5 2.0



Max output	790 W
Strokes per minute	High / Low: 2,000 / 1,500 min ⁻¹
Cutting strokes	High / Low: 4,000 / 3,000 min ⁻¹
Continuous use	High / Low: 90 / 160 min.
Blade Length	521 mm (20-1/2")
Handle height adjustment	3 stages (1,020 / 910 / 790mm, at 25mm cutting height)
Cutting height adjustment	Range: 25 - 105 mm (1 - 4-1/8")
Dimensions (L x W x H)	1,345 x 521 x 791 mm
Net weight	10 kg (22.1 lbs.)

40Vmax


XGT BL XPT

Blade cover, Hex wrench, Battery, Charger, Z: Battery and Charger are sold separately

UB004G

Cordless Backpack Blower



UB004GZ Cordless Backpack Blower

New

40Vmax XGT BL Cordless Variable 2-Speed Blower

Li-ion Ah 8.0 5.0 4.0 2.5 2.0



Blowing force	w/BL4080F x2: 0 - 17 / 23 N w/BL4080H x2: 0 - 17 / 32 N
Max air velocity	w/BL4080F x2: 81.4 m/s, w/BL4080H x2: 96.0 m/s
Avg. air velocity	0 - 58.2 / 68.0, 0 - 58.2 / 80.5 m/s
Air volume	0 - 13.6 / 16.2, 0 - 13.8 / 19.1 m ³ /min
Continuous use	w/BL4080F x2: 190 - 38 / 17 min., w/BL4080H x2: 190 - 38 / 14 min.
Dimensions (L x W x H)	242 x 585 x 522 mm (9-1/2 x 23 x 20-1/2")
Net Weight	8.8 kg (19.4 lbs.)

40Vmax


XGT BL XPT

End nozzle, Flat nozzle, Pipe support belt complete, Z: Battery and Charger are sold separately

- The blower runs on one battery at a time, and automatically switches to the second battery when the first one runs out
- Two speed modes with a tactile-feedback mode button
- The telescopic nozzle - adjustment over a range of 250 mm
- The redesigned backpack harness provides improved wearing comfort
- The narrow-diameter nozzle delivers high air velocity to clear even wet fallen leaves



UB003G

Cordless Blower



- Mode 2 for blowing and Mode 1 for vacuuming
- Tool-less switching between blower and vacuum with one-touch pipe locking.
- Dust bag with two zipper tabs for easier and wider opening during disposal.
- The blower nozzle length can be adjusted steplessly within a 130 mm range
- Cruise control lever to reduce finger fatigue



UB003GZ Cordless Blower

New

Maximum air volume is 13.8 m³/min for blowing and 13.0 m³/min for vacuuming

Li-ion Ah 8.0 5.0 4.0 2.5 2.0



Blower function	Max blowing force: 7 / 16N Max air volume: 9.4 / 13.8 m³/min Max air velocity: 0 - 46 / 68 m/s
Vacuum function	Max air volume: 13.0 m³/min Max suction power: 280 W Max sealed suction: 3.3 kPa
Dimensions (L x W x H)	699 - 830 x 201 x 400 mm (27-1/2 - 32-3/4 x 7-7/8 x 15-3/4")
Net weight	5.0 - 6.1 kg (11.0 - 13.4 lbs.)

40Vmax



XGT BL XPT



Flat nozzle, Vacuum kit, Band assembly, Hex wrench, Battery, Charger, Z: Battery and Charger are sold separately

UB005G

Cordless Blower Vacuum



UB005GZ Cordless Blower Vacuum

New

40Vmax XGT BL Cordless Variable-Speed Blower Vacuum

Li-ion Ah 8.0 5.0 4.0 2.5 2.0



Blower function	Max blowing force: 4.0 / 5.0 N Max air volume: 3.1 / 3.5 m³/min Max air velocity: 78.0 / 87.0 m/s
Vacuum function	Max air volume: 6.2 / 6.8 m³/min Avg. air velocity: 19 / 20 m/s Max suction power: 110 / 150 W Max sealed suction: 3.5 / 4.2 kPa
Dimensions (L x W x H)	1,169 x 184 x 412 mm
Net weight	4.4 kg (9.7 lbs.)




XGT BL XPT

40Vmax



Shoulder harness, Wide nozzle, Dust bag, Z: Battery and Charger are sold separately

- Two-speed modes with front-button selection
- Two wheels at the nozzle tip support ground travel for easier handling and help reduce wrist fatigue
- 25 L dust bag with a large opening for easy emptying
- A cruise-control lever helps reduce finger fatigue during continuous use
- Excellent balance for easy handling, even with a high-capacity BL4080F or BL4080H battery installed



UC031G

Cordless Chain Saw

XGT


DUC258

Cordless Chain Saw

LXT


UC031GZ 250mm (10") Cordless Chain Saw

New
40Vmax XGT Brushless Cordless Chain Saw
Li-ion Ah 5.0 | 4.0 | 2.5 | 2.0


Captive nuts type

Chain type	80T XL
Guide Bar Length	250 mm (10")
Chain Pitch	0.325"
Chain Gauge	1.1 mm (0.043")
Chain Speed	0 - 24.0 m/s
Oil tank capacity	150 mL (5.1 oz)
Dimensions (L x W x H)	w/o Guide Bar: 295 x 188 x 203 mm (11-5/8 x 7-3/8 x 8")
Net weight	3.2 - 3.8 kg (7.1 - 8.4 lbs.)

40Vmax

XGT **BL** **XPT**
4

 Saw chain, Guide bar case, Round file, Chain oil, Battery, Charger,
Z: Battery and Charger are sold separately

DUC258Z 250mm (10") Cordless Chain Saw

New
Excellent tool balance with optimal center of gravity
Li-ion Ah 6.0 | 5.0 | 3.0 | 1.5


Captive nuts type

Chain type	80T XL
Guide Bar Length	250 mm (10")
Chain Pitch	0.325"
Chain Gauge	1.1 mm (0.043")
Chain Speed	0 - 24.0 m/s
Oil tank capacity	140 mL (4.7 oz)
Dimensions (L x W x H)	w/o Guide Bar: 519 x 181 x 194 mm (20-1/2 x 7-1/8 x 7-5/8")
Net weight	3.0 kg (6.6 lbs.)

18V

LXT **BL** **XPT**
4

 Guide bar, Guide bar case, Saw chain, Box wrench, Round file, Chain oil, Battery, Charger,
Z: Battery and Charger are sold separately

BL
MOTOR

- 250mm top-handle chainsaw
- Fast acceleration in response to trigger operation enables smooth, continuous cutting tasks like pruning
- Adjustable automatic chain lubrication with 140 mL or 150 mL oil reservoir
- Hook for quick one-handed attachment and removal
- A shorter distance between the top handle and the center of gravity improves balance and reduces arm strain during horizontal cutting
- Equipped with both mechanical and electric brakes for user protection
- Captive nut prevents nut loss during guide bar or saw chain replacement

DUP181

Cordless Pruning Shears



- Equipped with a brushless motor, this tool cuts branches up to 30 mm in diameter, weighs only 1.1 kg
- Provides a slim grip with a 125 mm circumference
- Four adjustable opening angles to suit different branch sizes for enhanced efficiency
- Lubricating oil can be applied from the outside without disassembly
- Cutting depth can be adjusted after blade replacement



DUP181Z Cordless Pruning Shears

New

Four adjustable opening angles to suit different branch sizes

Li-ion Ah 6.0 5.0 3.0 1.5



Capacity	Max cutting: 30 mm (1-3/16")
Vibration level	2.5 m/s ² or less
Sound pressure level	70 dB (A) or less
Dimensions (L x W x H)	w/ BL1820B: 300 x 75 x 113 mm (11- 3/4 x 2-15/16 x 4-7/16")
Net weight	0.76 kg (1.7 lbs.)

18V



Blade cover, Hex wrench, Socket wrench, Z: Battery and Charger are sold separately

DTD158

Cordless Impact Driver



- Higher speed 3,400 RPM, More powerful 170 N·m (1,500 in.lbs.) and More compact 125 mm long
- BL motor delivers 3,400 max RPM and 170 N·m (1,500 in.lbs.) of max torque
- Compact and lightweight design
- Single LED light with preglow and afterglow functions
- Water-resistance compatible with XPT
- One-touch bit installation



DTD158RTJ / Z Cordless Impact Driver

New

Easy-to-Handle Basic Impact Driver with Optimal Battery location

Li-ion Ah 6.0 5.0 3.0 1.5



DTD158RTJ

1

DTD158Z

5

Capacity - Machine screw	M4 - M8 (5/32" - 5/16")
Standard Bolt	M5 - M16 (3/16" - 5/8")
High Strength Bolt	M5 - M14 (3/16" - 9/16")
Coarse thread (in length):	22 - 125 mm (7/8" - 4-7/8")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 3,400
Impacts Per Minute (IPM)	0 - 3,600
Max Fastening Torque	170 N·m (1,500 in.lbs.)
Sound Power Level	107 dB(A)
Dimensions (L x W x H)	125 x 81 x 233 - 251 mm (4-7/8 x 3-3/16 x 9- 1/8 - 9-7/8")
Net weight	1.3 - 1.6 kg (2.9 - 3.5 lbs.)

18V



Hook, Hand strap, Battery, Charger, Z: Battery and Charger are sold separately

DBN610

Cordless Finish Nailer

Finish Nail Capacity

Length:
32 - 64 mm

- 18V LXT Cordless 16 Ga 64 mm (2-1/2") Finish Nailer
- Rapid firing capability of 3.3 shots per second
- Drives a range of 16 gauge finish nails from 19 mm (3/4") to 64 mm (2-1/2"); magazine capacity up to 110 nails
- 2-mode selector switch for sequential or bump fire mode
- Slim nose with an easy-to-aim ejection section for better visibility when driving nails
- Anti-dry fire mechanism



DBN610Z Cordless Finish Nailer

New

18V LXT Cordless 16 Ga 64 mm (2-1/2") Finish Nailer

Li-ion Ah 6.0 5.0 3.0 1.5



Capacity	Length: 32 - 64 mm (1-1/4" - 2-1/2") Gauge: 16 Ga
Magazine Capacity	110 nails
Shot q'ty on a single full battery charge	1,100 pcs
Dimensions (LxWxH)	288 x 116 x 325 mm (11-3/8 x 4-9/16 x 12-3/4")
Net weight	3.0 - 3.3 kg (6.6 - 7.3 lbs.)

18V



LXT BL XPT

Nose adapter, Battery, Charger, Hook, Z: Battery and Charger are sold separately

DBN501

Cordless Brad Nailer

Brad Nail Capacity

Length:
15 - 50 mm

DBN501Z Cordless Brad Nailer

New

18V LXT Cordless 18 Ga 50 mm (2") Brad Nailer

Li-ion Ah 6.0 5.0 3.0 1.5



Capacity	Length: 15 - 50 mm (9/16" - 2") Gauge: 18 Ga
Magazine Capacity	110 nails
Shot q'ty on a single full battery charge	1,700 pcs
Dimensions (LxWxH)	246 x 96 x 301 mm (9-11/16 x 3-3/4 x 11-7/8")
Net weight	2.7 - 3.0 kg (6.0 - 6.6 lbs.)

18V



LXT BL XPT

Nose adapter, Battery, Charger, Hook, Z: Battery and Charger are sold separately

- 18V LXT Cordless 18 Ga 50 mm (2") Brad Nailer
- Rapid firing capability of 5.4 shots per second
- Drives a range of 18 gauge brad nails from 15 mm (9/16") to 50 mm (2"); magazine capacity up to 110 nails
- 2-mode selector switch for sequential or bump fire mode
- Slim nose with an easy-to-aim ejection section for better visibility when driving nails
- Anti-dry fire mechanism



DTM53

Cordless Multi Tool

STARLOCK
Compatible with
STARLOCK



DTM53RTJX1 / Z Cordless Multi Tool

New

Small diameter barrel grip for improved handling and comfort

Li-ion Ah 6.0 | 5.0 | 3.0 | 1.5




Oscillations Per Minute (OPM)	6,000 - 20,000 min ⁻¹
Oscillation Angle	3.2°
Depth gauge	Depth adjustment range: 0 - 50 mm (0 - 2") Height adjustment range: 8 - 95 mm (5/16 - 3-3/4")
Grip circumference	139 mm (5-1/2")
Dimensions (L x W x H)	329 x 80 x 120 mm (13 x 3-1/8 x 4-3/4")
Net weight	1.7 - 2.6 kg (3.7 - 5.7 lbs.)

18V



Oscillating multi tool accessories, Dust attachment, Battery, Charger, Z: Battery and Charger are sold separately

- With a brushless motor and constant speed control, the tool delivers high efficiency even under load
- Small diameter barrel grip for improved handling and comfort
- Tool-less clamp system for fast accessory installation
- Compatible with accessories in the Oscillating Interface System (OIS), and STARLOCK accessories
- 3.2° Oscillation angle
- 12 angle settings at every 30° from 0° to 360°



CL200FD

Cordless Cleaner



CL200FDSA / FDZ Cordless Cleaner

New

Vmax CXT Li-Ion Cordless 3-Speed Cleaner with LED Light

Li-ion Ah 5.0 | 4.0 | 2.0 | 1.5



Capacity	250 mL (8.5 oz)
Continuous Use (min.)	with BL1016: Max / High / Normal : 45 / 25 / 10 W
Max Air Flow	0.8 m ³ /min
Max Sealed Suction (water column)	14.0 kPa (N/A mmH ₂ O)
Dimensions (L x W x H)	1,031 x 90 x 151 mm (40-1/2 x 3-1/2 x 5-15/16")
Net weight	1.1 kg (2.4 lbs.)

12Vmax



Nozzle assembly, Sash nozzle, Nozzle holder, Pipe, High performance filter, Battery, Charger, DZ: Battery and Charger are sold separately

- 12Vmax CXT Li-Ion Cordless 3-Speed Cleaner with LED Light
- One-touch push button with Cyclone type
- Built-in small fan minimizes wind noise, and sound-absorbing sponge around the motor ensures low-noise performance
- Using a compact, high-speed BL motor for reduced weight and improved suction performance
- Single LED job light, functions also as battery capacity warning lamp
- Sash nozzle for cleaning corners and crevices of a car or furniture
- Convenient on-board sash nozzle storage
- Ideal for shop, office, hospital, airport, plane, station, train, home use, etc

191W05-0

Wheel Guard for Cup Diamond Wheel

- 125mm (5") Triple notches bearing box models
- Easy-to-see adjustable guide for greater accuracy
- Dust port can be adjusted 360 degrees for added versatility
- Attachment point on both sides for optional handle
- Durable, high quality metal construction for long life and added durability
- Base plate features a rounded lead edge for easier movement while making cuts
- Installs quickly and easily for added user convenience
- For use with Makita GA5050 GA005G Ga013G GA023G GA029G



E-23036

T.C.T. Saw Blade for Thin Metal

- T.C.T. Saw Blade 150 x 20mm x 57T
- Cutting efficiency is improved by reducing cutting resistance, thanks to thin tip and base metal
- By changing tip shape, the deformation and burr of the cut surface are reduced
- Ideal for cutting metal stud and sheet metal
- Longer life is realized by changing materials used for TCT
- For use with 150mm Cordless Metal Cutter DCS553 only



E-25046

Right Angle Attachment

- Tighten screws with ease in deep, tight, confined spaces
- Changes your fastening angle by 90°
- Compact design — perfect for tight spots
- High-durability build, compatible with XGT & LXT impact drivers
- 1/4" hex shank — works with impact drivers or sleeve chucks
- Design that based on Makita's angle driver



E-24985

Socket Adapter

- This 3-star range socket adapter let you downsize from a 3/4" drive impact wrench to a 1/2" drive socket with ease
- Large laser engraving makes it easy to see the size of the socket
- Made of chrome molybdenum impact resistant steel
- Designed for Impact Wrench use
- Ideal for professional use in workshops, industry, or automotive engineering



DLX2580J

18V LXT Combo Set

- 1 x Cordless Hammer Driver Drill DHP490Z
- 1 x Cordless Impact Driver DTD158Z
- 1 x Rapid Charger DC18RC
- 2 x 3.0Ah Battery BL1830B
- 1 x Makpac



DC18SJ

Battery Charger Set

- Battery charger for 14.4V/18V LXT batteries, powered by USB-PD (60W or higher)
- Compatible with USB-PD power supply (60W to 100W)
- For 14.4V/18V LXT batteries only
- Charging status indicator (Three colors: Red, Blue, Orange)
- 1 x Charger (1918B9-6), 1 x ADP14 Cigarette Adapter set, 1 x USB Type-C Cable 1m



D-63993

BiM Holesaw Assortment 16 pcs

- Holesaw sets developed according to the type of work, offered with new design cases
- Target for Electrician, Plumber, Metal Worker, Constructor, etc
- Able to fix Holesaw on protrusions with a thread ridge securely
- Consists of frequent used sizes of Holesaw for each type of work
- Holesaw: 16,19,22,25,32,35,37,44,51,57,64,68,76mm, 9.5mm hex arbor, 11mm hex arbor, ejector spring



E-26870

Plastic Case

- For convenient storage of screws, bits, and various small items
- The transparent lid allows for easy visibility of the contents, and the double-sided design
- Equipment repairman, construction worker, carpenter, DIY user etc
- The internal partitions of the case are removable, allowing the layout to be adjusted freely according to the items stored
- Size: 320x270x80mm



Makita®



**COMING
SOON**

Visit us at:
www.makita.com.sg



 MakitaSG